

AC/MC fittings

Quick-Lok™ connectors

QUICK-LOK™ CONNECTORS – STEEL

Features:

- No locknut required
- Single unit or duplex construction with captive clamp
- Connects 50 MC, AC and flex RW cable sizes with just three fittings
- Easy to install: tilt, insert and snap down
- Single unit construction eliminates loose component parts; integral green plastic insulated throat bushing provides maximum protection for wire installation


Standard material:

- Tubular steel

Standard finish:

- Zinc plated

UL File No. E-19188



Cable size

| Cat. # | Trade size | HCF | Aluminum and steel RWFMC/FMC | Cable dia. range | Unit qty. | Wt. lbs. per 100 |
|----------------------------------|-------------|--------------|------------------------------|------------------|-----------|------------------|
| QLK50S ² ¹ | 1/2" single | 14/2 to 10/3 | 3/8" | 0.385" - 0.600" | 50 | 8 |
| QLK50D ² ¹ | 1/2" duplex | 14/2 to 10/3 | 1/2" | 0.433" - 0.600" | 25 | 10 |
| QLK75 ² ¹ | 3/4" | 10/3 to 6/3 | 3/8" & 1/2" | 0.550" - 0.850" | 25 | 14 |

²UL approved for use with aluminum interlocking grounding metal-clad cable, Type MCIA (Southwire MCAP™). MCAP™ is a registered trademark of Southwire company.

¹UL approved for use with MC-PCS cable.