

# Condulet GUR conduit outlet boxes with covers

Cl. I, Div. 1 & 2, Groups C, D  
 Cl. II, Div. 1, Groups E, F, G  
 Cl. II, Div. 2, Groups F, G  
 Cl. III  
 NEMA 4

Explosionproof  
 Dust-ignitionproof  
 Raintight  
 Wet Locations

**3F**  
3F

## Applications:

GUR conduit outlet boxes are installed within hazardous areas:

- To protect conductors in threaded rigid conduit
- To act as pull and splice boxes
- To connect lengths of conduit
- To provide access to conductors for maintenance and future system changes
- To change conduit direction
- Where space is limited, such as underneath gasoline pumps

## Features:

GUR outlet boxes feature:

- Neoprene o-ring standard in cover to meet NEMA 4/UL Type 4 requirements
- Internal green ground screw #10
- Five standard hubs with three pipe plugs included
- Threaded cover opening
- Recesses in cover to assist in cover tightening and removal
- Smooth, integral hub bushing to protect conductor insulation when pulling
- Compact design for confined spaces
- UL and cUL Listed
- Optional all-aluminum construction

## Certifications and compliances:

### NEC/CEC:

- Class I, Divisions 1 & 2, Groups C, D
- Class II, Division 1, Groups E, F, G
- Class III
- Zones 1 & 2

### UL standard:

- UL1203

### CSA standard:

- cUL to CSA standard C22.2 No. 30

### Environmental rating:

- NEMA 4

## Standard materials:

- Bodies – Feraloy iron alloy
- Covers – copper-free aluminum

## Standard finishes:

- Feraloy iron alloy – electrogalvanized with aluminum acrylic paint
- Aluminum – natural

## Options:

- | Description                           | Suffix    |
|---------------------------------------|-----------|
| • Bodies – copper-free aluminum ..... | <b>SA</b> |

## Accessories (ordered separately):

- | Description               | Cat. #          |
|---------------------------|-----------------|
| • Replacement gasket..... | <b>GASK1801</b> |



## Ordering information:

Hub size	Cat. #
1/2"	<b>GUR1</b>
3/4"	<b>GUR2</b>
1"	<b>GUR3</b>

## Dimensions (in inches):

