


TYPE PBTS

Features

- Broad wire range: 750kcmil-14
- UL Listed and CSA Certified for 600 volts, 90° C
- Dual rated
- Cold temperature rated to -45° C
- High dielectric strength plastisol
- Black cover
- Removable plugs
- Prefilled with De-ox®

Benefits

- Flexibility in the field
- Ensures reliability
- For copper or aluminum conductor
- Application variability
- Chemical resistant
- UV Rated
- Entry port closure
- Prevents oxides from forming



D

Catalog Number	No. Of Ports	Wire Range	Dimensions			Hex Size
			L	W	H	
PBTS-10-3/0	10	3/0-6	8.00	1.58	1.86	3/16
PBTS-11-3/0	11	3/0-6	8.77	1.58	1.86	3/16
PBTS-12-3/0	12	3/0-6	9.54	1.58	1.86	3/16
PBTS-13-3/0	13	3/0-6	10.30	1.58	1.86	3/16
PBTS-14-3/0	14	3/0-6	11.07	1.58	1.86	3/16
PBTS-2-250	2	250kcmil-6	2.17	1.91	2.17	5/16
PBTS-3-250	3	250kcmil-6	3.07	1.91	2.17	5/16
PBTS-4-250	4	250kcmil-6	3.96	1.91	2.17	5/16
PBTS-5-250	5	250kcmil-6	4.85	1.91	2.17	5/16
PBTS-6-250	6	250kcmil-6	5.75	1.91	2.17	5/16
PBTS-7-250	7	250kcmil-6	6.64	1.91	2.17	5/16
PBTS-8-250	8	250kcmil-6	7.53	1.91	2.17	5/16
PBTS-9-250	9	250kcmil-6	8.42	1.91	2.17	5/16
PBTS-10-250	10	250kcmil-6	9.32	1.91	2.17	5/16
PBTS-11-250	11	250kcmil-6	10.21	1.91	2.17	5/16
PBTS-12-250	12	250kcmil-6	11.10	1.91	2.17	5/16
PBTS-13-250	13	250kcmil-6	12.00	1.91	2.17	5/16
PBTS-14-250	14	250kcmil-6	12.89	1.91	2.17	5/16
PBTS-2-350	2	350kcmil-6	2.51	2.03	2.62	5/16
PBTS-3-350	3	350kcmil-6	3.56	2.03	2.62	5/16
PBTS-4-350	4	350kcmil-6	4.61	2.03	2.62	5/16
PBTS-5-350	5	350kcmil-6	5.66	2.03	2.62	5/16
PBTS-6-350	6	350kcmil-6	6.71	2.03	2.62	5/16
PBTS-7-350	7	350kcmil-6	7.76	2.03	2.62	5/16
PBTS-8-350	8	350kcmil-6	8.81	2.03	2.62	5/16
PBTS-9-350	9	350kcmil-6	9.86	2.03	2.62	5/16
PBTS-10-350	10	350kcmil-6	10.91	2.03	2.62	5/16
PBTS-11-350	11	350kcmil-6	11.96	2.03	2.62	5/16
PBTS-12-350	12	350kcmil-6	13.01	2.03	2.62	5/16
PBTS-13-350	13	350kcmil-6	14.06	2.03	2.62	5/16
PBTS-14-350	14	350kcmil-6	15.11	2.03	2.62	5/16
PBTS-2-500	2	600kcmil-4	2.97	2.28	3.04	3/8
PBTS-3-500	3	600kcmil-4	4.12	2.28	3.04	3/8
PBTS-4-500	4	600kcmil-4	5.28	2.28	3.04	3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Per NEC Article 310-316, allowable ampacities are as follows: #4-95 Amps, 1/0-170 Amps, 3/0-225 Amps, 250-290 Amps, 350-350 Amps, 500-430 Amps, 750-535 Amps

Replacement caps & plugs available. Consult Factory Tested to UL 486A/B, UL File E6207