
# Wiring Space


## **Typical Panelboard**

Front view with trim removed




### Typical Front w/Concealed Hinges and Trim Adjusting Screws

Surface mounting – add 1/4" to inside box dimensions Flush mounting – add 1 1/2" to inside box dimensions



#### Typical Box



## Minimum Wiring Space, From End of Lug to Box Wall, in Inches

	Main rating in amos	Ena wali		Frame	Mounting	Main Circuit Breaker Phase Lug
		Phase Lug	Neutral Lug	туре	5	To End Wall
	500A (1)	15	11 (1)	SG	Vertical	16
	800A <sup>(2)</sup>	15	11 (1)	SK	Vertical	18

(1) Box width is 30" and 7.81" deep

#### Wiring Space - Branch Circuit Breakers

Branch Circuit Devices	Frame	No. of Poles	Minimum Wiring Spaces To Side Wall (30" Wide Box)
Double Branched Bolt-on Devices	FB, TED, THED	1,2,3	8.25"
Double branched bolt-on Devices	SE	2,3	8.25"
Horizontal Single Branch Mounted	SFHA, SFLA	2,3	7.5"
Horizontal Single Branch Mounted	SGHA, SGLA	2,3	8.5"

#### Enclosures

Panel Size	Box	Front	
Fuller Size	Cat. No. (1)	Size Inches (2)	Cat. No. (3)
0-25.5	AB25BDW	25.5	AF25F,S
28.5-31.5	AB31BDW	31.5	AF31F,S
34.5-37.5	AB37BDW	37.5	AF37F,S
40.5-43.5	AB43BDW	43.5	AF43F,S
46.5-49.5	AB49BDW	49.5	AF49F,S
52.5-55.5	AB55BDW	55.5	AF55F,S
58.5-64.5	AB64BDW	64.5	AF64F,S
67.5-76.5	AB76BDW	76.5	AF76F,S
79.5-82.5	AB82BDW	82.5	AF82F,S
85.5-88.5	AB88BDW	88.5	AF88F,S

(1) "B" suffix provides blank end walls. Order "K" suffix for endwalls with knockouts.

(2) Standard boxes are 30" wide by 7.81" deep.

(3) Flush fronts are 1 1/2" larger than box. Surface fronts are 1/4" larger.

#### **Box Options**

Description	Cat. No. Suffix (1)		
Painted Box	Р		
30" wide <sup>(2)</sup>	W		
NEMA 3R/12/4S/4X	3 or 4		
NEMA 4X (316 Stainless Steel)	4S		

Add to base box product number.
Includes field installable gutter barrier.

#### Permanent Circuit Number Kits

Description	Cat. No.
1-48	APN48
43-84	APN84
85-126	APN126

## **Front Options**

Description	Cat. No. Suffix (1)	
Screw cover	С	
Front hinged to box	D	
Yale 5116 w/Rosette Lock	Y	
Corbin 15767 Lock	L	
GE 75 Key Lock	E	(1
Corbin 60 Key Lock	J	(2
Door within a door <sup>(2)</sup>	Р	(2
Stainless steel (3)	S	
30" wide	W	
Nameplate	Ν	
Screw on nameplate	U	(3
Metal directory	М	

L) Add to base front catalog number. 2) Consists of two lockable doors—one over panel interior and one over box wiring gutters. Yale locks not available. 3) Flush only. Available with C and N options.

## **Stainless Steel Enclosures**

Dimensions (inches)			Cat No.		
Н	W	D	UL Standard	CSA Labeled	
25.5	30	8	AB254DWS	AB254DWAS	
31.5	30	8	AB314DWS	AB314DWAS	
37.5	30	8	AB374DWS	AB374DWAS	
43.5	30	8	AB434DWS	AB434DWAS	
49.5	30	8	AB494DWS	AB494DWAS	
55.5	30	8	AB554DWS	AB554DWAS	
64.5	30	8	AB644DWS	AB644DWAS	
76.5	30	8	AB764DWS	AB764DWAS	