

## Service Entrance Cable

### Connectors and Entrance Heads



CI808 / CI816

CI806

CI804



Zinc Die Cast Locknut



Zinc Die Cast Locknut



Cat. No.	Trade Size (in.)	Clamping Range (in.)		Throat (in.)
		Min.	Max.	
<b>Two Screw Fittings (Zinc Alloy)</b>				
CI804	3/8	0.18	0.64	0.64
CI806	3/4	0.41	0.82	0.83
CI808	1	0.50	1.04	1.05
CI810	1-1/4	0.56	1.06	1.37
CI812	1-1/2	0.63	1.60	1.81
CI816	2	0.86	2.06	2.05

NOTE : 3/8 in. trade size connectors require a 1/2 in. knockout.

### CIEFA-1/2 / CIEFA-4




CIEFSA-1/2 / CIEFSA-4



Cat. No.	Trade Size (in.)
<b>Service Entrance Heads (Cast Aluminum)</b>	
<b>Rigid Conduit</b>	
CIEFA-1/2	1/2
CIEFA-3/4	3/4
CIEFA-1	1
CIEFA-1 1/4	1-1/4
CIEFA-1 1/2	1-1/2
CIEFA-2	2
CIEFA-2 1/2	2-1/2
CIEFA-3	3
CIEFA-3 1/2	3-1/2
CIEFA-4	4
<b>Service Entrance Heads (Cast Aluminum)</b>	
<b>EMT</b>	
CIEFSA-1/2	1/2
CIEFSA-3/4	3/4
CIEFSA-1	1
CIEFSA-1 1/4	1-1/4
CIEFSA-1 1/2	1-1/2
CIEFSA-2	2
CIEFSA-2 1/2	2-1/2
CIEFSA-3	3
CIEFSA-3 1/2	3-1/2
CIEFSA-4	4

Trade Size (in.)	KO Dimensions (in.)		
	Small	Large	Center
1/2	0.312	—	—
3/4	0.375	0.400	—
1	0.438	0.500	—
1-1/4	0.438	0.625	—
1-1/2	0.610	0.750	0.400
2	0.750	1.000	0.525
2-1/2	0.875	1.300	1.000
3	1.125	1.750	1.125
3-1/2	1.125	1.750	1.125
4	1.125	1.750	1.125



## EMT

### Conduit Fittings, Accessories and Entrance Heads



#### CILRL-1/2 / CILRL-2

#### CITA-1/2 / CITA-2



Combined LL/LR  
Left and right  
application



Cat. No.	Trade Size (in.)	Dimensions (in.)		
		A	B	C
<b>EMT Conduit Fittings - "LRL" Type (Cast Aluminum)</b>				
CILRL-1/2	1/2	4-7/16	1-11/16	2-1/8
CILRL-3/4	3/4	5-3/16	1-7/8	2-1/4
CILRL-1	1	6	2-3/16	2-1/2
CILRL-1-1/4	1-1/4	7-15/16	2-3/4	3-1/2
CILRL-1-1/2	1-1/2	7-15/16	3-1/4	3-1/2
CILRL-2	2	10-3/16	3-11/16	4-1/8
<b>EMT Conduit Fittings - "T" Type (Cast Aluminum)</b>				
CITA-1/2	1/2	4-7/8	1-3/8	2-1/16
CITA-3/4	3/4	5-9/16	1-3/4	2-1/8
CITA-1	1	6-1/2	2	2-1/2
CITA-1-1/4	1-1/4	8-11/16	2-5/8	3-1/2
CITA-1-1/2	1-1/2	8-11/16	3	3-9/16
CITA-2	2	10-7/8	3-1/4	4-3/16

Covers and gaskets are included with all aluminum conduit fittings  
Types CILRL and CITA are also suitable for use with rigid conduit

#### CIBC-1/2 / CIBC-2



Cat. No.	Trade Size (in.)
<b>Blank Covers for Aluminum Conduit Fittings (Stamped Aluminum)</b>	
CIBC-1/2	1/2
CIBC-3/4	3/4
CIBC-1	1
CIBC-1-1/4	1-1/4
CIBC-2	2

For 1-1/2, use CIBC-1-1/4

#### CIG-1/2 / CIG-2



Cat. No.	Trade Size (in.)
<b>Gaskets for Aluminum Conduit Fittings (Neoprene)</b>	
CIG-1/2	1/2
CIG-3/4	3/4
CIG-1	1
CIG-1-1/4	1-1/4
CIG-2	2

For 1-1/2, use CIG-1-1/4

#### CIEFSA-1/2 / CIEFSA-4



Cat. No.	Trade Size (in.)
<b>Service Entrance Heads (Cast Aluminum)</b>	
CIEFSA-1/2	1/2
CIEFSA-3/4	3/4
CIEFSA-1	1
CIEFSA-1-1/4	1-1/4
CIEFSA-1-1/2	1-1/2
CIEFSA-2	2
CIEFSA-2-1/2	2-1/2
CIEFSA-3	3
CIEFSA-3-1/2	3-1/2
CIEFSA-4	4

Consult page D10 for technical specifications