



# Lamp Data

## General Information

Lamp Type	Part Number	Catalog Suffix	Voltage	Watts	Lumen Rating	Center-Beam Candle Power (CBCP)	Beam Angle (Degrees)	Bulb Type
<b>MR16 Halogen Lamps</b> 	580.0072	MH	6	5.4	34	73	36	MR16
	580.0074	MI	6	6	40	130	24	MR16
	580.0079	MJ	6	10	77	790	16	MR16
	580.0099	MO	12	10	86	200	36	MR16
	580.0080	MK	12	12	135	320	36	MR16
	580.0064	MG	12	20	270	525	36	MR16
	580.0075	MA	12	20-A	245	600	36	MR16
	580.0068	MW	12	20-H	417	950	36	MR16
	580.0083	MB	12	35	490	3300	24	MR16
	580.0076	MC	12	50	785	2800	24	MR16
	580.0089	MM	12	50-H	1550	5700	24	MR16
	580.0070	MS	24	12	95	280	36	MR16
	580.0077	MD	24	20	240	740	24	MR16
	580.0094	MN	24	20-A	195	890	24	MR16
	580.0084	ME	24	35	460	990	36	MR16
	580.0078	MF	24	50	875	3200	24	MR16
	580.0065	MT	120	20	100	240	36	MR16
	580.0066	MU	120	35	230	520	36	MR16
	580.0067	MV	120	50	460	1100	36	MR16
	<b>MR16 LED Lamps</b> 	580.0097	LA	6	4	130	600	24
580.0093		LG	12	4	170	440	30	MR16
580.0096		LH	12	4	170	700	24	MR16
580.0098		LL	24	4	200	900	24	MR16
580.0095		LV	120	4	200	900	24	MR16
Lamp Type	Part Number	Catalog Suffix	Voltage	Watts	Lumen Rating	Total Candle Power (CP)	Lamp #	Bulb Type
<b>EXIT Signs, Hazardous Locations Incandescent Lamps</b>	580.0086	XX6	6	15	210	17	JC6V-15W2K	Bi-Pin G4
	570.0071	XX12	12	25	375	30	13769	A19
	570.0118	XX24	24	25	345	27	24227-1	A19
	570.0136	AC	120	25	215	17	97478	A19
Lamp Type	Part Number	Voltage	Watts	Lumen Rating	Total candle power (CP)	Lamp #	Base Type	
<b>EXIT Signs, 120Vac Incandescent</b>	570.0013	145	15	150	12	15T6145	Candelabra Screw Base	
	570.0024	120	20	90	7	20T61/2	Intermediate Screw Base	
	570.0035	145	15	150	12	15T6	Intermediate Screw E17	
	595.0010	120	7	330	26	PL7-T4	G23	

**Important:** Lumen rating and candle power values are only for general reference. The data was obtained from the manufacturer's catalogs, calculations or third-party laboratory measurements. Actual performance in the field may and will vary.

### Explosion-Proof Incandescent Lamps

Item P/N	Catalog Suffix	Voltage	Watts	Lumen Rating	Lamp #
580.0086	XX6	6	15	225	JC-6V15W
570.0071	XX12	12	25	378	-
570.0118	XX24	24	25	345	-
570.0136	AC	120	25	215	-


### 120 Volt AC Exit Lamps

Lamp Type	Catalog	Watts	Lamp #	Base
Incandescent	570.0013	15	15T6145	Candelabra Screw Base
Incandescent	570.0024	20	20T61/2	Intermediate Screw Base
Incandescent	570.0035	15	15T6	Intermediate Screw Base
Fluorescent	595.0010	7	PL7-T4	G23


### MSA Incandescent Lamp Adapter

#### For HIT, DCBB or Bi-Pin Halogen Lamps


DC lamp plus adapter for medium Edison screw base socket. This device converts any incandescent fixture into an emergency fixture.



MSA Bi-Pin



MSA Double Contact



MSA Wedge Base

### How to Order (example)

MSA	HB
Product Code	Lamp Symbol

Note:  
Lumen figures based on information supplied by lamp manufacturers.  
Lamp drawings shown are for shape comparison only, not actual size.