

Flex-Plus® Blue™ ENT

Flex-Plus® Blue™ ENT is a nonmetallic flexible raceway for use in walls, floors and non-plenum ceilings. It's lightweight, hand bendable and free from sharp edges, which reduces installation time and saves money.

- Ideal storage conditions down to -20°C

(See page I59 for technical information.)

Options

- Sizes 1/2 in. through 2 in.
- Colours can designate different voltages
- Yellow colour for communication circuits and signaling cable
- Red colour for fire alarm circuits
- Blue colour for power circuits



Standard Stock – Reels

Cat. No.	Size (in.)	Colour	Nom. I.D. (in.)	Nom. O.D. (in.)	Pull Tape	Min. Bend Radius	Reel Type (W=Wood)	Reel Length	Reel Wt. (lb.)	Wt. per 100 ft. (lb.)
1205AKC-001	1/2	Blue	0.56	0.84	Empty	36 x 24	W	1500	40	10
1207AAC-001	3/4		1000	40				14		
12008C-750	1		750	40				20		
12009C-750	1-1/4		750	90				19		
12009C-500	1-1/4		500	90		19				
12010C-750	1-1/2		750	90		39				
12011C-500	2		500	90		32				
12011C-225	2		225	90		32				

1-1/4 in. - 2 in. available in yellow & red, made to order; contact your Regional Sales Office.

Standard Stock – Coils

Cat. No.	Size (in.)	Colour	Nom. I.D. (in.)	Nom. O.D. (in.)	Pull Tape	Min. Bend Radius	Coil Length (ft.)	Wt. per 100 ft. (lb.)
12005C-200	1/2	Blue	0.56	0.84	Empty	6	200	10
12005C-370	1/2		6	370		10		
12007C-100	3/4		6	100		14		
12007C-240	3/4		6	240		14		
12008C-160	1		6	160		22		
12009C-500C	1-1/4		7	500		19		
12010C-300C	1-1/2		8-1/4	300		39		
12011C-225C	2		9-1/2	225		32		

NOTE: The solid blue colour of ENT conduit is a registered trademark of Carlton®.

ENT may show colour deterioration in direct sunlight when stored outdoors over an extended period of time. It is suggested that all ENT products not be stored outside.