

### Global Plus Connector Cables



### Global Plus Connector Cables

#### Product Description

Finish your sensor installation with high quality connector cables from Eaton's Electrical Sector. Our Global Plus line is designed to give you everything you want without paying extra for the features you don't want. It includes a wide variety of single- and double-connector cables. Custom lengths are available upon request from the factory.

#### Standards and Certifications

- UL Recognized (Mini-Style)
- CSA Certified (Mini- and Nano-Styles)
- cUL Recognized (Micro- and Nano-Styles)



### Contents

<i>Description</i>	<i>Page</i>
Global Plus Connector Cables	
Product Selection Guide . . . . .	<b>V8-T10-4</b>
Catalog Number Selection . . . . .	<b>V8-T10-4</b>
Product Selection	
Single Connector Cables . . . . .	<b>V8-T10-5</b>
Double Connector Cables . . . . .	<b>V8-T10-8</b>
Receptacles—Micro and Mini . . . . .	<b>V8-T10-9</b>
Accessories . . . . .	<b>V8-T10-9</b>
Technical Data and Specifications . . . . .	<b>V8-T10-10</b>
Wiring Diagrams . . . . .	<b>V8-T10-10</b>
Dimensions . . . . .	<b>V8-T10-11</b>

#### **DANGER**

**THIS SENSOR IS NOT A SAFETY DEVICE AND IS NOT INTENDED TO BE USED AS A SAFETY DEVICE. This sensor is designed only to detect and read certain data in an electronic manner and perform no use apart from that, specifically no safety-related use. This sensor product does not include self-checking redundant circuitry, and the failure of this sensor product could cause either an energized or de-energized output condition, which could result in death, serious bodily injury, or property damage.**

For the most current information on this product, visit our Web site: [www.eaton.com](http://www.eaton.com)

For Customer Service in the U.S. call 1-877-ETN CARE (386-2273), in Canada call 1-800-268-3578.  
For Application Assistance in the U.S. and Canada call 1-800-426-9184.

### Product Selection

#### Single Connector Cables

##### Micro-Style Straight Female



#### Micro-Style Straight Female

Voltage Style	Number of Pins	Gauge	Length	Pin Configuration/Wire Colors (Face View Female Shown)	PVC Jacket Catalog Number	PUR Jacket Catalog Number			
<b>Standard Cables</b>									
AC	3-pin, 3-wire	18 AWG	6.0 ft (2m)		CSAS3F3CY1802	—			
			16.4 ft (5m)		CSAS3F3CY1805	—			
			32.8 ft (10m)		CSAS3F3CY1810	—			
		22 AWG	6.0 ft (2m)		CSAS3F3CY2202	CSAS3F3RY2202			
			16.4 ft (5m)		CSAS3F3CY2205	CSAS3F3RY2205			
			32.8 ft (10m)		CSAS3F3CY2210	CSAS3F3RY2210			
			4-pin, 4-wire		18 AWG	6.0 ft (2m)		CSAS4F4CY1802	—
						16.4 ft (5m)		CSAS4F4CY1805	—
						32.8 ft (10m)		CSAS4F4CY1810	—
	22 AWG	6.0 ft (2m)		CSAS4F4CY2202	CSAS4F4RY2202				
		16.4 ft (5m)		CSAS4F4CY2205	CSAS4F4RY2205				
		32.8 ft (10m)		CSAS4F4CY2210	CSAS4F4RY2210				
		22 AWG		4-pin, 4-wire	6.0 ft (2m)		CSAS4A4CY2202	—	
							16.4 ft (5m)	CSAS4A4CY2205	—
							32.8 ft (10m)	CSAS4A4CY2210	—
22 AWG	5-pin, 5-wire	6.0 ft (2m)		CSAS5A5CY2202	—				
				16.4 ft (5m)	CSAS5A5CY2205	—			
				32.8 ft (10m)	CSAS5A5CY2210	—			
DC	4-pin, 3-wire	22 AWG	6.0 ft (2m)		CSDS4A3CY2202	CSDS4A3RY2202			
			16.4 ft (5m)		CSDS4A3CY2205	CSDS4A3RY2205			
			32.8 ft (10m)		CSDS4A3CY2210	CSDS4A3RY2210			
	4-pin, 4-wire	22 AWG	6.0 ft (2m)		CSDS4A4CY2202	CSDS4A4RY2202			
			16.4 ft (5m)		CSDS4A4CY2205	CSDS4A4RY2205			
			32.8 ft (10m)		CSDS4A4CY2210	CSDS4A4RY2210			
			65.6 ft (20m)		CSDS4A4CY2220	—			
			5-pin, 5-wire		22 AWG	6.0 ft (2m)		CSDS5A5CY2202	—
								16.4 ft (5m)	CSDS5A5CY2205
	32.8 ft (10m)	CSDS5A5CY2210		—					
	8-pin, 8-wire	24 AWG	16.4 ft (5m)		CSDS8A8CB2405	—			
			32.8 ft (10m)		CSDS8A8CB2410	—			