For a complete assembly, please select:

Select for standard applications

Switch

Switch amp rating	No. of poles	SCCR	Max horsepower rating 1-phase 120 Vac	1-phase 220/240Vac	3-phase 220/240Vac	3-phase 440/480Vac	3-phase 600 Vac	Wire size	Wire type	Part number
30	3	100kA	2	5	10	20	25	#10-2/0 Str #12-10 Sol	75°C Cu	RD30-3
60	3	100kA	3	10	20	40	50	#10-2/0 Str #12-10 Sol	75°C Cu	RD60-3
100	3	25/100kA*	5	10	20	50	50	#10-2/0 Str #12-10 Sol	75°C Cu	RD100-3

* 100kA @480Vac, 25kA @ 600Vac.

+

Handles

Direct mount handle - mounts directly to switch, no shaft required

For switch part number	Color		Test function	Padlockable		Part number
All switches	Black		N	Y - On Switch		DIR-02

or



External front or right side operated selector handles - shaft required

NEMA type	Color	Handle length	Test function	Padlockable		Part number
1, 3R, 4, 4X, 12	Black	Short	N	Y		H4X-01B(1)
1, 3R, 4, 4X, 12	Red/yellow	Short	N	Y		H4X-01R(1)
1, 3R, 4, 4X, 12	Black	Long	N	Y		H4X-02B(2)
1, 3R, 4, 4X, 12	Red/yellow	Long	N	Y		H4X-02R(2)

or

External front operated pistol handles - shaft required

NEMA type	Color	Handle length	Test function	Padlockable	Defeatable	Part number
1, 3R, 4, 4X, 12	Black	—	N	Y	Y	H4X-03B
1, 3R, 4, 4X, 12	Red/yellow	—	N	Y	Y	H4X-03R

Metallic hasp (heavy duty) external front operated pistol handles - shaft required

NEMA type	Color	Handle length	Test function	Padlockable	Defeatable	Part number
1, 3R, 4, 4X, 12	Black	—	N	Y	Y	H4X-03BHD
1, 3R, 4, 4X, 12	Red/yellow	—	N	Y	Y	H4X-03RHD

+



Shafts for selector handles

Length in (mm)	Mounting depth (X) in (mm)		Part number
5.9 (150)	3.50~7.60 (89~193)		SH4-150(1)
7.9 (200)	3.50~9.50 (89~241)		SH4-200(1)
12.6 (320)	3.50~14.9 (89~378)		SH4-320(1)

+

Shafts for pistol handles

Length in (mm)	Mounting depth (X) in (mm)		Part number
7.9 (200)	3.30~7.40 (84~188)		SH3-200(2)
12.6 (320)	3.30~9.30 (84~236)		SH3-320(2)
15.7 (400)	3.30~14.7 (84~373)		SH3-400(2)

Shaft guide for selector handles

	Part number
Required for 12.6" (320mm) long shafts, optional for other lengths	SH-GUIDE1

Shaft guide for pistol handles

	Part Number
Required for 15.7" (400mm) long shafts, optional for other lengths	SH-GUIDE2

and …

Acc's — Aux contacts

Auxillary contacts

Contact type	Number of contacts	Continuous amp rating	Voltage rating	Max number of Units per switch	Part number
NO + NC	1 of each	10A	240Vac	2 (1 per side/4 contacts total)	BAC01
NO	2	10A	240Vac	2 (1 per side/4 contacts total)	BAC02