

Cover Control

Product Selection

Type 1 Non-Combination Cover Control (Box 1 Only)

- Cover control for non-combination starters uses M22 style devices as standard
- Pushbuttons are momentary type
- Field convertible selector switches from momentary to maintained operation and vice versa
- Cover control kits include hardware, M22 pushbuttons, bracket and pre-wired wire harnesses
- See Volume 7, Tab 1, for more details on M22 pushbuttons

Type 1 Non-Combination Cover Control (Box 1 Only)

Box 1 offering includes metallic enclosures with starters up to 32 A.



Description	Factory Installed	Field Installation Kits
	Flange Control Position 9 Cover Control Code	Catalog Number
Non-Reversing		
No cover mounted pilot devices	A	—
STOP/START oval pushbuttons	B	C600M1
With red RUN pilot light	C	C600M101 ^①
With red RUN/green OFF lights	D	C600M102 ^①
OFF/ON oval pushbuttons	E	C600M2
With red RUN pilot light	F	C600M201 ^①
With red RUN/green OFF lights	G	C600M202 ^①
STOP/START selector switch	S	C600M13
With red RUN pilot light	T	C600M131 ^①
With red RUN/green OFF lights	U	C600M132 ^①
OFF/ON selector switch	V	C600M14
With red RUN pilot light	W	C600M141 ^①
With red RUN/green OFF lights	X	C600M142 ^①
HAND/OFF/AUTO selector switch	H	C600M12
With red RUN pilot light	J	C600M121 ^①
With red RUN/green OFF lights	K	C600M122 ^①
Green START pushbutton	L	C600M3
Red STOP pushbutton	Y	C600M7 ^①
Green ON pushbutton	M	C600M4
Red OFF pushbutton	N	C600M5
Red RUN pilot light	P	C600M9 ^①
Green OFF pilot light	Q	C600M10 ^①
Red RUN/green OFF lights	R	C600M11 ^①
TEST/OFF/AUTO selector switch	—	C600M8
Reversing		
UP/STOP/DOWN selector switch	E	C600M27
With 2 red pilot lights	F	C600M271 ^①
REV/STOP/FWD selector switch	H	C600M15
With 2 red pilot lights	J	C600M151 ^①
Two red pilot lights (labeled FWD, REV)	P	C600M28 ^①
Green OFF pilot light	Q	C600M10 ^①

Note

^① Add code letter from the table below to catalog number for voltage. Example: C600M101A.

Rating	Code Letter
85–264 Vac	A
480 Vac	C
12–30 Vac/Vdc	T