

# Weatherproof receptacle covers

## Industrial specification grade device covers


### Product description

Metal covers for FS/FD boxes


### Deluxe weatherproof covers for FS/FD boxes

#### Features


- UL Listed for wet locations (cover closed) and damp locations (cover open or closed)
- Meets 2014 NEC® 406.9 (A) and 406.9 (B)(2)
- Diecast copper free aluminum with epoxy finish provides maximum corrosion resistance
- Self-closing spring door assures full protection
- EPDM gasketing material on WLRD1 and WLRS1 provide excellent resistance to ozone, weathering and temperatures from -46° C to 127° C (-50° F to 260° F)




WLRD1



WLRS1



7420



7420CR

### Diecast aluminum receptacle covers



#### Description

Duplex receptacle cover, horizontal mounting

#### Catalog no.

□ WLRD1

Single receptacle cover, vertical mounting, 1.38" (34.9mm) face diameter, use with 15A, 20A straight blade and 15A Hart lock receptacles

□ WLRS1

Single receptacle cover, vertical mounting, 1.56" (39.7mm) face diameter, use with 20A and 30A Hart lock receptacles

□ WLRS2

### Standard weatherproof covers for FS/FD boxes

#### Features

- UL Listed for wet locations (cover closed) and damp locations (cover open or closed)
- Meets 2014 NEC® 406.9 (A) and 406.9 (B)(2)
- Self-closing spring door assures full protection
- Gasketing material provides excellent resistance to weather
- Duplex covers can be used with any duplex receptacle

### Diecast aluminum receptacle covers



#### Description

Duplex receptacle cover, vertical mounting

#### Catalog no.

□ AH7879\*

Single receptacle cover, vertical mounting, 1.38-1.56" (34.9-39.7mm) face diameter, use with 15A and 20A single straight blade receptacles and 15A, 20A and 30A single Hart lock receptacles

□ 7420



Single receptacle cover, vertical mounting, 1.38-1.56" (34.9-39.7mm) face diameter, yellow corrosion resistant finish, used with 15A and 20A single straight blade receptacles and 15A, 20A and 30A single Hart lock receptacles

□ 7420CR

Single receptacle, vertical mounting for 2.12" (53.8mm) face diameter, use with 30A straight blade receptacles

□ 7420A

\* Not UL Listed

Note: Cat. no. 7420, 7420CR have inserts for protecting toggle; can be used with most standard length toggle switches.

Compliances, specifications and availability are subject to change without notice.



Indicates NAFTA compliant - Page Q-30