

A.  
About  
Panduit

B.  
Copper  
Systems

C.  
Fiber  
Systems

D.  
Faceplates,  
Outlet  
Frames &  
Surface  
Mount Boxes

E.  
Keystone  
Cabling  
Systems

F.  
Zone  
Cabling

G.  
Cable  
Routing  
Systems

H.  
Surface  
Raceway

J.  
Cabinets,  
Racks &  
Cable  
Management  
Systems

K.  
Power  
Management

L.  
Grounding  
&  
Bonding

M.  
Identification  
Products

N.  
Cable  
Management  
Accessories

O.  
Part  
Number  
Index

## Wyr-Grid® Accessories

- Offered in three different heights: 2" (50mm), 4" (102mm), and 6" (152mm)
- Standard finishes are black powder coat and electro zinc plated



WGSW2BL



WGSW4BL



WGSW6BL



WGINTBRC2BL



WGINTBRC4BL



WGINTBRC6BL



WGHRDWKTBL

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
-------------	------------------	----------------	----------------

### Wyr-Grid® Pathway Snap-On Sidewalls

WGSW2BL	Wyr-Grid® 2" (50mm) high Snap-On Sidewalls can be attached anywhere along the pathway where needed to retain cables.	1	40
WGSW4BL	Wyr-Grid® 4" (102mm) high Snap-On Sidewalls can be attached anywhere along the pathway where needed to retain cables.	1	40
WGSW6BL	Wyr-Grid® 6" (152mm) high Snap-On Sidewalls can be attached anywhere along the pathway where needed to retain cables.	1	40

### Wyr-Grid® Pathway Intersection Bend Radius Controls

WGINTBRC2BL	Wyr-Grid® 2" (50mm) high Snap-On Intersection Bend Radius Control provides 3" (76mm) bend radius control and can be installed without cutting or fabrication at tees, crosses, and right angle intersections.	1	—
WGINTBRC4BL	Wyr-Grid® 4" (102mm) high Snap-On Intersection Bend Radius Control provides 3" (76mm) bend radius control and can be installed without cutting or fabrication at tees, crosses, and right angle intersections.	1	—
WGINTBRC6BL	Wyr-Grid® 6" (152mm) high Snap-On Intersection Bend Radius Control provides 3" (76mm) bend radius control and can be installed without cutting or fabrication at tees, crosses, and right angle intersections.	1	—

For electro zinc finish replace BL (Black) with EZ.

### Wyr-Grid® Hardware

WGHRDWKTBL	The hardware kit is used when field fabricating a right angle, allowing large radii to be created by cutting the pathway, bending it, and securing it into a right angle. 12" (305mm) width requires 6 pieces to create a 15.8" radius. 18" (457mm) width requires 9 pieces to create a 24.4" radius. 24" (610mm) width requires 12 pieces to create a 33.4" radius. 30" (762mm) width requires 15 pieces to create a 41.5" radius.	1	10
------------	---	---	----

Available in BL (Black) only.

A.  
About  
Panduit

B.  
Copper  
Systems

C.  
Fiber  
Systems

D.  
Faceplates,  
Outlet  
Frames &  
Surface  
Mount Boxes

E.  
Keystone  
Cabling  
Systems

F.  
Zone  
Cabling

G.  
Cable  
Routing  
Systems

H.  
Surface  
Raceway

J.  
Cabinets,  
Racks &  
Cable  
Management  
Systems

K.  
Power  
Management

L.  
Grounding  
&  
Bonding

M.  
Identification  
Products

N.  
Cable  
Management  
Accessories

O.  
Part  
Number  
Index



### Power Rated Fittings for Power to 600 V — LDPH/LDS/LD2P Raceway Only



Part Number	Part Description	Color‡	Std. Pkg. Qty.
CFX3IW-X	Coupler fitting for use with LDPH3 raceway.	Off White	10
CFX5IW-X	Coupler fitting for use with LDPH5 raceway.	Off White	10
CFX10IW-X	Coupler fitting for use with LD10 raceway.	Off White	10
RAFX3IW-X	Right angle fitting for use with LDPH3 raceway.	Off White	10
RAFX5IW-X	Right angle fitting for use with LDPH5 raceway.	Off White	10
RAFX10IW-X	Right angle fitting for use with LDPH10 raceway.	Off White	10
ICFX3IW-X	Inside corner fitting for use with LDPH3 raceway.	Off White	10
ICFX5IW-X	Inside corner fitting for use with LDPH5 raceway.	Off White	10
ICFX10IW-X	Inside corner fitting for use with LDPH10 raceway.	Off White	10
OCFC3IW-X	Outside corner fitting for use with LDPH3 raceway.	Off White	10
OCFC5IW-X	Outside corner fitting for use with LDPH5 raceway.	Off White	10
OCFC10IW-X	Outside corner fitting for use with LDPH10 raceway only.	Off White	10
TFX3IW-X	Tee fitting for use with LDPH3 raceway.	Off White	10
TFX5IW-X	Tee fitting for use with LDPH5 raceway.	Off White	10
TFX10IW-X	Tee fitting for use with LDPH10 raceway only.	Off White	10
CRFX5IW-X	Four-way cross fitting for use with LDPH5 raceway.	Off White	10
CEFXIW-X	Conduit entrance end fitting. This power rated two-piece fitting is designed to accommodate the entrance of 1/2" conduit or align with knockouts on surface mount electrical boxes. For use with LD3/LDPH3 and has breakouts available to work with LD5/LDPH5 and LD10/LDPH10. Cover and base snap together — no hardware is required.	Off White	10
ECFX3IW-X	End cap fitting for use with LDPH3 raceway.	Off White	10
ECFX5IW-X	End cap fitting for use with LDPH5 raceway.	Off White	10
ECFX10IW-X	End cap fitting for use with LDPH10 raceway.	Off White	10
DCEFXIW-X	Drop ceiling/entrance end fitting for use with LD3, LDPH3, LD5, LDPH5, LD10 and LDPH10 raceway. Use CA3IW-X or CA5IW-X adapters for LD3 or LD5 profile raceway.	Off White	10
RAEFXIW-X	Right angle/entrance end fitting for use with LD3, LDPH3, LD5, LDPH5, LD10 and LDPH10 raceway. CA3IW-X or CA5IW-X adapters for LD3 or LD5 profile raceway.	Off White	10
RFX53IW-X	Reducer fitting for use with LD3, LDPH3, LDS3, LD5, LDPH5 and LDS5 raceway. For in-line terminations, use with CFX5IW-X.	Off White	10
RFX103IW-X	Reducer fitting for use with LD3, LDPH3, LD10 and LDPH10 raceway. For in-line terminations, use with CFX10IW-X.	Off White	10
RFX105IW-X	Reducer fitting for use with LD5, LDPH5, LD10 and LDPH10 raceway. For in-line terminations, use with CFX10IW-X.	Off White	10

‡For other colors replace IW (Off White) with EI (Electric Ivory) or WH (White).

See D-SRSG02--WW-ENG, Surface Raceway Selection Guide or D-SRLC01--WW-ENG, Surface Raceway line card for additional information.