

Intended Use

Use in high mounting heights that require high efficiencies, horizontal illumination and premium glare control. Ideal for general manufacturing areas and warehouse aisles.

Features

- Die-cast aluminum housing
- Integral splice box mounting flange ensures structural integrity
- A17: premium spun aluminum anodized 17" reflector

- PA22 or PA22L: high-performance UV-stabilized prismatic acrylic refractor (available lensed or open)
- Electronic HID ballasts are 100% factory-tested
- 3/4" threaded hub for suspended mounting with rigid conduit (other mounting options available)

Listings

UL and cUL Listed for damp locations, 40°C ambient.

RHMC A17

RHMC PA22



With lens option

Example: RHMC 210MP A17 208 HEB CR

ORDERING INFORMATION

Specifications subject to change.

Series	Wattage ²	Reflector	Voltage	Ballast
RHMC ¹	Protected metal halide	A17 Open aluminum	208	HEB
	210MP 210W ^{2,3}	PA22 Open acrylic	240	
	315MP 315W ²	PA22L Lensed (tempered glass acrylic)	277	
			TVOLT	

Options	Finish
SF Single fuse (277) ⁴	(blank) Textured dark gray with aluminum accents
DF Double fuse (208, 240) ⁴	DNA Gloss natural aluminum with aluminum accents
EC Emergency circuit ^{4,5,6}	DBLB Textured black with aluminum accents
QRS Quartz restrike system ^{4,5,6}	DWH Gloss white
LCPP Loop, cord, plug requires TPH, PPH ⁴	CR Corrosion-resistant finish
LC3P Loop, 3' cord, 15A NEMA [®] twist-lock plug ⁴	
HC3P Hook, 3' cord, 15A NEMA twist-lock plug ⁴	

LOCS Loop, 5' white cord, RELOC [®] OCS ^{4,7}	GL17 Tempered glass lens ⁹	
HOCs Hook, 5' white cord, RELOC OCS ^{4,7}	GL17WG Tempered glass lens with wireguard ⁹	
LOCU Loop, 5' white cord, RELOC OCU ^{4,7}	DIM Dimming access terminal	
HOCU Hook, 5' white cord, RELOC OCU ^{4,7}	CSA Listed and labeled to comply with Canadian Standards	
W/Lamp 210W or 315W lamp ⁸	NOM NOM Certified (consult factory)	
Q150DC QRS lamp for 210W ⁸		
Q175DC QRS lamp for 315W ⁸		

ADDITIONAL INFORMATION

For additional product information, visit www.lithonia.com.

ACCESSORIES

ORDER SEPARATELY

HKF	Fixture hook female
LPF	Fixture loop female
SCK	60" safety chain kit
WGA17	Wireguard ⁹
HKM	Fixture hook male
HKMG	Grommited fixture hook male
LPM	Fixture loop male
LPMG	Grommited fixture loop male
TPH	Through-wire power hook ¹⁰
PPH	Pendant power hook ¹⁰
DCY	Cylinder shade
DSQ	Square shade
DHX	Hexagonal shade

Notes

- Lamp not included.
- These wattages comply with California Title 20.
- Dimming over 25% of operational time not recommended by lamp/ballast manufacturer.
- Must specify voltage.
- Quartz lamp max wattage is 150 for 210M. QRS max wattage is 250 for 315M.
- Option is not field-installable. Must be factory-installed.
- May be ordered with 10', 15' and 20' cords. For black cord, specify BK (i.e.: HOCsBK).
- Will ship as separate line item.
- When ordering GL17 option, wireguard must be factory-installed on glass.
- Must use with LCPP.

Certain airborne contaminants can diminish integrity of acrylic and polycarbonate. Refer to the Acrylic & Polycarbonate Environmental Compatibility tables on pages 1116-1117 for suitable uses.