# Flexible Metallic Conduit Fittings

# Squeeze Type - Malleable Iron

# **SQUEEZE TYPE - MALLEABLE IRON**

# **Applications:**

• Used to squeeze and secure AC/MC cable to a box or enclosure

#### **Features:**

- High strength malleable iron
- 105°C temperature rating
- · Used with armoured cable and flexible metal conduit
- Male threads NPSM

#### **Standard Materials:**

- Malleable iron
- Steel locknut

#### **Standard Finish:**

• Zinc plated

### Squeeze Type\* - Straight - Non-insulated

UL File No. E-19189







Cat. #	Trade Size	Dia. of Opening for Cable	Dia. of Bushed Hole	Unit Qty.	Wt. Lbs. Per 100
707†§	3/8″	5/8″	3/8″	100	7
708‡§	1/2"	<sup>15</sup> / <sub>16</sub> "	5/8″	50	14
709	3/4"	1 1/8″	3/4"	20	22
710	1"	1³/ <sub>8</sub> ″	1"	20	31
711	11/4"	1 <sup>21</sup> / <sub>32</sub> "	15/16"	10	46
712	11/2"	1 <sup>7</sup> /8"	11/2"	5	79
713	2"	21/2"	2"	2	101
714	21/2"	27/8"	23/8"	2	161
715	3"	39/16"	3"	1	220
721	31/2"	4"	213/32"	1	470
722	4"	419/32"	331/32"	1	610

<sup>\*</sup>UL Listed flexible metallic conduit fittings are suitable as grounding means under NEC 350-5 and suitable for hazardous location use per Class I, Division 2, NEC 501-4(b). †Suitable for use with armoured cable.

MCAP™ is a registered trademark of Southwire Company.

## Squeeze Type - Straight - Insulated\*

UL File No. E-19189







Cat. #	Trade Size	Dia. of Opening for Cable	Dia. of Bushed Hole	Unit Qty.	Wt. Lbs. Per 100
1707†§	³/ <sub>8</sub> ″	5/8″	3/8″	100	8
1708‡§	1/2"	1 <sup>5</sup> / <sub>16</sub> "	5/8″	50	14
1709	3/4"	11/8″	3/4"	20	17
1710	1"	1³/ <sub>8</sub> "	1"	20	26
1711	11/4"	121/32"	1 <sup>5</sup> / <sub>16</sub> "	10	42
1712	11/2"	1 <sup>7</sup> /8"	11/2"	5	77
1713	2"	21/2"	2"	2	100
1714	21/2"	27/8"	23/8"	2	160
1715	3"	39/16"	3"	1	221
1721	31/2"	4"	313/32"	1	470
1722	4"	419/32"	331/32"	1	610

<sup>\*</sup>UL Listed flexible metallic conduit fittings are suitable as grounding means under NEC 350-5 and suitable for hazardous location use per Class I, Division 2, NEC 501-4(b). †Suitable for use with armoured cable.



<sup>\$</sup>Suitable for use with metal-clad cable.

<sup>\$</sup>UL approved for use with aluminum interlocking grounding metal-clad cable, Type MCIA (Southwire MCAP\*).

<sup>‡</sup>Suitable for use with metal-clad cable. §UL approved for use with aluminum interlocking grounding metal-clad cable, Type MCIA (Southwire MCAP™).
MCAP™ is a registered trademark of Southwire Company.