Series C

K-Frame and HMCP (K) Auxiliary Switch

		Factory Mounted Connection Type and Location 18-Inch (457.2 mm) Pigtail Leads			Terminal Block	Field Mounted Factory Installation Kit ^① Pigtail Leads	1) Terminal Block
Number of Contacts A and B	Mounting Location (Pole)	Same Side Suffix Number	Rear ^② Suffix Number	Opposite Side Suffix Number	Same Side Suffix Number	Catalog Number	Catalog Number
1	Left	A01	A02	A03	A04	A1X3PK	A1X3LTK
	Right 23	A05	A06	A07	A08	A1X3PK	A1X3RTK ④
2	Left	A09	A10	_	A11	A2X3PK	A2X3LTK
	Right ©3	A12	A13	_	A14	A2X3PK	A2X3RTK ④
	Right	A21	A22	_	_	1482D28G10 67	_
3	Left	A18	_	_	A15	A3X3LPK	A3X3LTK
	Right ⁽³⁾	A17	_	_	A16	A3X3RPK	A3X3RTK ④

L-, HMCP (L) and (M) Frames and Auxiliary Switch

		Factory Mounted Connection Type and Location 18-Inch (457.2 mm) Pigtail Leads			Terminal Block	Field Mounted Factory Installation H Pigtail Leads	(it ^① Terminal Block
Number of Contacts A and B	Mounting Location (Pole)	Same Side Suffix Number	Rear [©] Suffix Number	Opposite Side Suffix Number	Same Side Suffix Number	Catalog Number	Catalog Number
1	Left	A01	A02	A03	A04	A1X4PK	A1X4LTK
	Right @	A05	A06	A07	A08	A1X4PK	A1X4RTK ④
2	Left	A09	A10	_	A11	A2X4PK	A2X4LTK
	Right ⁽²⁾	A12	A13	_	A14	A2X4PK	A2X4RTK ④
3	Left	A18	_	_	A15	A3X4PK	A3X4LTK
	Right ⁽²⁾	A17	_	_	A16	A3X4PK	A3X4RTK ④

N-Frame and HMCP (N) Auxiliary Switch

		Factory Mounted Connection Type and Location 18-Inch (457.2 mm) Pigtail Leads			Terminal Block	Field Mounted Factory Installation Kit Pigtail Leads	① Terminal Block
Number of Contacts A and B	Mounting Location (Pole)	Same Side Suffix Number	Rear [©] Suffix Number	Opposite Side Suffix Number	Same Side Suffix Number	Catalog Number	Catalog Number
1	Left	A01	A02	A03	A04	A1X5PK	A1X5LTK
	Right ⁽²⁾	A05	A06	A07	A08	A1X5PK	A1X5RTK ④
2	Left	A09	A10	—	A11	A2X5PK	A2X5LTK
	Right ⁽²⁾	A12	A13	_	A14	A2X5PK	A2X5RTK ④
3	Left	A18	_	_	A15	A3X5LPK	A3X5LTK
	Right ⁽²⁾	A17	_	_	A16	A3X5RPK	A3X5RTK ④

R-Frame Auxiliary Switch (RH Only)

	Factory Mounted Connection Type and Location	Field Mounted Field Installation Kits ${f \widehat{u}}$		
Number of	18-Inch (457.2 mm) Pigtail Leads	Pigtail Leads		
Contacts A and B	Suffix Number ®	Catalog Number ®		
2	A12	A2X6RPK		
4	A19	A4X6RPK		

Notes

① Listed with Underwriters Laboratories for field installation under E64983.

② Standard mounting location—leads exit rear of breaker.

 $\ensuremath{^{\textcircled{3}}}$ Breakers with K-Frame OPTIM 550 can only accept accessories in left pole.

④ Not for use on four-pole circuit breakers.

[®] A maximum of two auxiliary switches (any combination of 2a/2b or 4a/4b plug-in modules may be installed in a circuit breaker.

[®] This option is not field installable.

 $^{\odot}\;$ Available on the OPTIM 550 only. Communications are not available with this option.