Specifications for 3M™ Double Coated Foam Tapes (continued)

Product Number	Product Description (Backing/Adhesive)	Tape Thickness	Temperature Resistance		Typical Applications
Urethane			**Min./Hr.**	**Days/Week**	
4004	Off-white, open-cell urethane foam carrier. Features high-shear adhesive with high-temperature resistance.	0.250" (6,4 mm)	380°F (193°C)	220°F (104°C)	• Bond mirrors to walls or furniture. • Bond acoustic panels to walls. • Mount air fresheners. • Mount soap dispensers. • Mount interior signs and nameplates. • Attach wire clips to various surfaces. • Mount electrical channel to wall surfaces. • Vibration damping for electronic components. • Die cut pieces.
4008	Off-white, open-cell urethane foam carrier. Features high-shear adhesive with high-temperature resistance.	0.125" (3.2 mm)	380°F (193°C)	220°F (104°C)	
4016	Off-white, open-cell urethane foam carrier. Features high-shear adhesive with high-temperature resistance.	0.062" (1,6 mm)	380°F (193°C)	220°F (104°C)	
4026	Off-white, open-cell urethane foam carrier. Features high-shear adhesive with high-temperature resistance.	0.062" (1,6 mm)	380°F (193°C)	220°F (104°C)	
4032	Off-white, open-cell urethane foam carrier. Features high-shear adhesive with high-temperature resistance.	0.031" (0,8 mm)	380°F (193°C)	220°F (104°C)	
4042	Off-white, open-cell urethane foam carrier. Features high-tack adhesive.	0.031" (0,8 mm)	200°F (93°C)	150°F (66°C)	
4046	Off-white, open-cell urethane foam carrier. Features high-tack adhesive.	0.062" (1,6 mm)	200°F (93°C)	150°F (66°C)	
4052	Black version of 4032 tape.	0.031" (0,8 mm)	380°F (193°C)	220°F (104°C)	
4056	Black version of 4016 and 4026 tapes.	0.062" (1,6 mm)	380°F (193°C)	220°F (104°C)	
4085	Off-white, open-cell urethane foam carrier. Features high-tack adhesive.	0.045" (1,1 mm)	200°F (93°C)	125°F (52°C)	• Core starting on metal cores.
9579	Double coated high-tack hand-tearable film tape. 3-mil polyethylene film carrier. Rubber adhesive	0.009" (0.25 mm)	150°F (65°C)	120°F (49°C)	• Splicing rough or coated material.

Ordering Information for 3M™ Double Coated Foam Tapes
(continued)

Product Number	UPC (021200-)	Size	Inner Unit Pack	Case Qty.
Double Coated Urethane Foam Tape				
4082	25217	1/2" x 72 yd. (13 mm x 66 m)	rolls	18
4082	25218	3/4" x 72 yd. (19 mm x 66 m)	rolls	12
4085	17660	1/2" x 72 yd. (13 mm x 66 m)	rolls	18
4085	17661	3/4" x 72 yd. (19 mm x 66 m)	rolls	12
4085	17662	1" x 72 yd. (25,4 mm x 66 m)	rolls	9
Double Coated Tape				
9579	65869	2" x 36 yd. (51 mm x 33 m)	rolls	24
9579	65870	1 1/2" x 36 yd. (38 mm x 33 m)	rolls	24
9579	65871	1" x 36 yd. (25,4 mm x 33 m)	rolls	36
9579	65872	3/4" x 36 yd. (19 mm x 33 m)	rolls	48
9579	65873	1/2" x 36 yd. (13 mm x 33 m)	rolls	72
Dispensers				
M-744	11089	Definite Length Dispenser - 2"	each	1
M-87	11038	Definite Length Dispenser - Electric - 1"	each	1
M-89	13020	Definite Length Dispenser - Electric Foam - 1"	each	1