



Description

Non-IC rated remodel housing for applications where the back side of the ceiling is not accessible • Designed to be installed in non-insulated areas, or where insulation is spaced at least 3" from housing

Listings

UL Listed, cUL/CSA certified for through-branch wiring, damp and wet locations • Wet location listed with the 210N, 211, and 212N trims • Wet location listed with trims 215 and 216 when used with PAR30 outdoor rated lamps • Conforms with City of Chicago IP requirements

Features

- 5" Remodel housing
- Medium base porcelain socket with nickel-plated copper screw shell
- Drop socket with spring to accommodate various trim installations
- Remodel springs accommodate up to a 1 1/8" ceiling thickness
- Housing is fully assembled for ease of installation
- Pre-wired junction box with (5) 1/2" knockouts with pryout slots, (4) non-metallic sheathed cable connectors, and ground wire
- Shadow-free, knife-edge trim design blends smoothly into the ceiling
- UL Listed, cUL/CSA certified for through-branch wiring, maximum (4) #12 AWG branch circuit conductors (2 in, 2 out)
- Thermally protected against improper use of lamps or insulation
- Lamp wattage ratings and apertures based on trim selection. Trim selection follows IC20 and TC20 Series

Ordering Information

Catalog No.	Description
TC20R	5" TC Incandescent remodel housing

Ordering Information

Catalog No.	Description
SMPLT-5	Galvanized steel plate for locating remodel style housings. Screw/nail holes for full coverage between 16" and 24" joists

Dimensions

