

# Motor Starters for Use in the Field, High Degree of Protection

## ET 200pro Motor Starters

### ET 200pro – interface modules

#### Selection and ordering data

Version	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*	PG
<b>IM 154-1 and IM 154-2 interface modules</b>						
<b>IM 154-1 interface modules</b> For ET 200pro; for communication between ET 200pro and higher-level masters over PROFIBUS DP	A	<b>6ES7154-1AA01-0AB0</b>		1	1 unit	250
<b>IM 154-2 High-Feature interface modules</b> For ET 200pro; for communication between ET 200pro and higher-level masters over PROFIBUS DP; support of PROFIsafe	A	<b>6ES7154-2AA01-0AB0</b>		1	1 unit	250
<b>Accessories</b>						
<b>CM IM DP ECOFAST connection modules</b> For connection of PROFIBUS DP and 24 V power supply to PROFIBUS interface modules, two ECOFAST Cu connections	A	<b>6ES7194-4AA00-0AA0</b>		1	1 unit	250
<b>CM IM DP Direct connection modules</b> For direct connection of PROFIBUS DP and 24 V power supply to PROFIBUS interface modules, up to six M20 screwed cable glands	A	<b>6ES7194-4AC00-0AA0</b>		1	1 unit	250
<b>CM IM DP M12 7/8" connection module</b> For connection of PROFIBUS DP and 24 V power supply to PROFIBUS interface modules, 2 x M12 and 2 x 7/8"	A	<b>6ES7194-4AD00-0AA0</b>		1	1 unit	250
<b>Accessories for CM IM DP ECOFAST</b>						
<b>PROFIBUS ECOFAST hybrid cables, assembled</b> With 2 ECOFAST connectors, trailing cable With 2 x Cu 0.64 mm <sup>2</sup> and 4 x Cu 1.5 mm <sup>2</sup>						
• Length 1.5 m	A	<b>6XV1830-7BH15</b>		1	1 unit	5K2
• Length 3.0 m	A	<b>6XV1830-7BH30</b>		1	1 unit	5K2
• Length 5.0 m	A	<b>6XV1830-7BH50</b>		1	1 unit	5K2
• Length 10 m	A	<b>6XV1830-7BN10</b>		1	1 unit	5K2
• Length 15 m	A	<b>6XV1830-7BN15</b>		1	1 unit	5K2
• Length 20 m	A	<b>6XV1830-7BN20</b>		1	1 unit	5K2
• Length 25 m	A	<b>6XV1830-7BN25</b>		1	1 unit	5K2
• Length 30 m	A	<b>6XV1830-7BN30</b>		1	1 unit	5K2
• Length 35 m	A	<b>6XV1830-7BN35</b>		1	1 unit	5K2
• Length 40 m	A	<b>6XV1830-7BN40</b>		1	1 unit	5K2
• Length 45 m	D	<b>6XV1830-7BN45</b>		1	1 unit	5K2
• Length 50 m	D	<b>6XV1830-7BN50</b>		1	1 unit	5K2
<b>PROFIBUS ECOFAST hybrid cables GP, assembled</b> With 2 ECOFAST connectors, trailing cable With 2 x Cu 0.64 mm <sup>2</sup> and 4 x Cu 1.5 mm <sup>2</sup>						
• Length 1.5 m	A	<b>6XV1860-3PH15</b>		1	1 unit	5K2
• Length 3.0 m	A	<b>6XV1860-3PH30</b>		1	1 unit	5K2
• Length 5.0 m	D	<b>6XV1860-3PH50</b>		1	1 unit	5K2
• Length 10 m	A	<b>6XV1860-3PN10</b>		1	1 unit	5K2
• Length 15 m	A	<b>6XV1860-3PN15</b>		1	1 unit	5K2
• Length 20 m	A	<b>6XV1860-3PN20</b>		1	1 unit	5K2
• Length 25 m	A	<b>6XV1860-3PN25</b>		1	1 unit	5K2
• Length 30 m	A	<b>6XV1860-3PN30</b>		1	1 unit	5K2
• Length 35 m	A	<b>6XV1860-3PN35</b>		1	1 unit	5K2
• Length 40 m	A	<b>6XV1860-3PN40</b>		1	1 unit	5K2
• Length 45 m	A	<b>6XV1860-3PN45</b>		1	1 unit	5K2
• Length 50 m	A	<b>6XV1860-3PN50</b>		1	1 unit	5K2
<b>PROFIBUS ECOFAST hybrid cables, non-assembled</b> Trailing cable with 2 x Cu 0.64 mm <sup>2</sup> and 4 x Cu 1.5 mm <sup>2</sup>						
• Length 50 m	A	<b>6XV1830-7AN50</b>		1	1 unit	5K2
• Length 100 m	A	<b>6XV1830-7AT10</b>		1	1 unit	5K2
<b>PROFIBUS ECOFAST hybrid cables GP, non-assembled</b> Trailing cable with 2 x Cu 0.64 mm <sup>2</sup> and 4 x Cu 1.5 mm <sup>2</sup>						
• Length 50 m	B	<b>6XV1860-4PN50</b>		1	1 unit	5K2
• Length 100 m	A	<b>6XV1860-4PT10</b>		1	1 unit	5K2
<b>PROFIBUS ECOFAST hybrid connectors 180</b> ECOFAST Cu, 2 x Cu, 4 x 1.5 mm <sup>2</sup> , HANBRID connectors						
• With pin insert, pack of 5	A	<b>6GK1905-0CA00</b>		1	5 units	5K2
• With female insert, pack of 5	A	<b>6GK1905-0CB00</b>		1	5 units	5K2
<b>PROFIBUS ECOFAST hybrid connectors, angular</b> ECOFAST Cu, 2 x Cu, 4 x 1.5 mm <sup>2</sup> , HANBRID connectors						
• With pin insert, pack of 5	A	<b>6GK1905-0CC00</b>		1	5 units	5K2
• With female insert, pack of 5	A	<b>6GK1905-0CD00</b>		1	5 units	5K2