Canvas Tapered-Bottom Bag

- No. 10 canvas.
- Two pockets are provided for small parts.
- Bottom is tapered so parts will stay in center.
- Equipped with a snap for hanging.

Cat. No.	Diameter	Depth	Weight (lbs.)
5143	6-1/2" (165 mm)	8" (203 mm)	.30



5143

Hooks

Swivel Snap Hook

Additional Features:

- This is NOT an occupational protective hook. NOT for human support.
- Bronze swivel snap hook made for use on canvas buckets.
- Maximum safe load is 150 lbs. (68 kg).

Cat. No.	Length	Width	Weight (lbs.)
2012	4-3/8" (111 mm)	1-5/8" (41 mm)	.28



2012

AWARNING: This is NOT an occupational protective device. NOT for human support.

Hook for Aerial-Baskets

- All weather, durable, nylon 66 polymer.
- Most manufacturers' aerial basket trucks accommodate bucket hook.
- Replacement hook for both Cat. No. 5144 and Cat. No. 5169.

Cat. No.	Weight (lbs.)
5144H	.30



Slings

Pole Sling



5606

- For use where a running loop wrap around pole is desired.
- Nylon web stitched with nylon thread.
- Copper rivets with burrs at the point of wear.
- NOT an occupational protective device.
 NOT for human support.
- Resistant to oil, creosote, and moisture.

Cat. No.	Rated Capacity (Maximum Working Load)		Overall Length	Width	Weight (lbs.)
	Choke Hitch	Basket Hitch			
5606	3000 lbs (1350 kg)	4700 lbs (2115 kg)	39" (991 mm)	2" (51 mm)	1.33

AWARNING: This is NOT an occupational protective device. NOT for human support.

Crossarm Sling



- Made of 12 plies of nylon laminated together with neoprene and pre-formed prior to vulcanization for ease in placing around the crossarm.
- D-rings are 1/4" (6 mm) welded wire securely riveted with copper rivets and burrs.
- NOT an occupational protective device. NOT for human support.
- Resistant to oil, creosote, and moisture.

Cat. No.	Rated Capacity (Maximum Working Load) Basket Hitch	Overall Length	Width	Weight (lbs.)
5607	1000 lbs (450 kg)	23-1/4" (590 mm)	1" (25 mm)	.83

AWARNING: This is NOT an occupational protective device. NOT for human support.