


















Contact blocks

		Cat. no.	Ref. no.
<b>Logic Reed</b>	Contact type	NC	<b>P9B01FH</b> 187014
		NO	<b>P9B10FH</b> 187015
A new range of LOGIC REED contact blocks with faston terminals for use with power lower than 12V - 5mA.	Rated voltage	AC2 to 120V max. DC2 to 30V max.	
	Rated current	AC/DC - 0.001 to 0.15A max.	
	Rated power	AC - 8VA max. DC - 4.5W max.	
	Minimum centerline distance	30x32 mm.	
	Mounting on operators	through specific bayonet flange adaptor.	<b>P9ACFSM</b> 187846
	Full voltage power supply		<b>P9PDHF</b> 187056

	With screw	Contact type	Cat. no.	Ref. no.
Intro	 min. 1 of 22 AWG (0.32 mm <sup>2</sup> ) max. 2 of 12 AWG (3.3 mm <sup>2</sup> )			
A		1 3 2 4 	<b>P9B11VN</b>	187000
B		1 1 2 2 	<b>P9B02VN</b>	187008
C		3 3 4 4 	<b>P9B20VN</b>	187009
D		1 2 	<b>P9B01VN</b>	187001
E		3 4 	<b>P9B10VN</b>	187002
F		1 2 	<b>P9B01VR</b>	187003
G		3 4 	<b>P9B10VA</b>	187004
H	<b>Faston</b>	1 2 	<b>P9B01FN</b>	187012
I	 1 x (6.35 x 0.8 mm) 2 x (2.8 x 0.8 mm)	3 4 	<b>P9B10FN</b>	187013
J/X	<b>Terminal adapter</b>		<b>P9ACA6</b>	188804
	printed circuit board adapter			

The catalogue numbers in **bold** are available from stock.

