

Low voltage, branch circuit fuses

Time-delay Low-Peak CUBEFuse™ finger-safe fuse

TCF 600V Class CF



Specifications:

Description: Finger-safe fuse and fuse holder system; dual-element, time-delay fuse; 10 seconds minimum operating time at 500% rated amps.

Dimensions: See dimensions illustration.

Poles: 1-pole (gangable)

Ratings:

Volts — 600Vac (or less)
— 300Vdc (or less)

Amps — 1-100A

IR — 300kA RMS Sym. (UL)
— 200kA RMS Sym. (CSA)
— 100kA DC (UL and CSA)

Agency information: CE, UL Listed Guide JDDZ, File E4273, CSA Certified Fuse: Class 1422- 02, File 53787, UL Listed Fuse holder: Guide IZND, File E214079, CSA Certified Fuse holder: Class 6225-01, File 47235.

Features and benefits:

- Separate overload and short-circuit elements provide time delay for sizing of high inrush loads linked with Class J current limitation.
- Selective coordination ratio of 2:1 (within Low-Peak fuse family) prevents electrical shutdowns from extending beyond the failed circuit.
- Smallest footprint of any Class CC, J, T or RK fuse provides substantial space savings and installation flexibility.
- IEC 60529 and finger-safe rating provides enhanced workplace safety.

Typical applications:

- Electrical panelboards
- Machinery disconnects
- Industrial control
- Required finger-safe systems

Fuse catalog numbers indicating (amps)

TCF6	TCF25	TCF50	TCF100
TCF10	TCF30	TCF60	
TCF15	TCF35	TCF70	
TCF17-½	TCF40	TCF80	
TCF20	TCF45	TCF90	

Fuse catalog numbers non-indicating (amps)

TCF1RN	TCF17-½RN	TCF40RN	TCF80RN
TCF3RN	TCF20RN	TCF45RN	TCF90RN
TCF6RN	TCF25RN	TCF50RN	TCF100RN
TCF10RN	TCF30RN	TCF60RN	
TCF15RN	TCF35RN	TCF70RN	

Carton quantity and weight

Amp rating	Carton qty.	Weight per carton	
		lbs	kg
1-30A	12	1.39	0.63
35-60A	12	1.42	0.65
70-100A	6	1.74	0.79

Recommended fuse holders for Class CF fuses

- See page 1-16

Data Sheet: 9000 (fuses) and 9007 (holders)