

Type CBL Bolt-On Loadcentres

Non-Combination (Main Lug Only) Single & Three Phase Aluminum Bus

Single Phase 120/240VAC Type 1 (Indoor) Loadcentres

- ◆ CSA Certified only (Not UL Approved)
- ◆ Utilize Type BAB, QBHW, QBA, DNBA, or QBGF circuit breakers as branch circuit breakers.

Product Selection

Table 41. Single Phase 3 Wire 120/240VAC Aluminum Bus Loadcentres

Maximum Ampere Rating	Catalogue Number	Max. No. 1" Spaces	Max. No. 1/2" Spaces	Cover Style	Dimensions (Inches / mm)			Wire Size Range for Main Cu/Al
					H	W	D	
125	CBL118	18	36	Flush/Surface	27 / 685.8	14-1/4 / 361.9	3-3/4 / 95.3	#6-300MCM
125	CBL130	30	60	Flush/Surface	34-1/8 / 866.8	14-1/4 / 361.9	3-3/4 / 95.3	#6-300MCM
125	CBL142	42	84	Flush/Surface	39 / 990.6	14-1/4 / 361.9	3-3/4 / 95.3	#6-300MCM
225	CBL218	18	36	Flush/Surface	27 / 685.8	14-1/4 / 361.9	3-3/4 / 95.3	#6-300MCM
225	CBL230	30	60	Flush/Surface	34-1/8 / 866.8	14-1/4 / 361.9	3-3/4 / 95.3	#6-300MCM
225	CBL242	42	84	Flush/Surface	39 / 990.6	14-1/4 / 361.9	3-3/4 / 95.3	#6-300MCM

Three Phase 240VAC Type 1 (Indoor) Loadcentres

- ◆ CSA Certified only (Not UL Approved)
- ◆ Utilize Type BAB, QBHW, QBA, DNBA, or QBGF circuit breakers as branch circuit breakers.

Product Selection

Table 42. Three Phase 4 Wire 240VAC Aluminum Bus Loadcentres

Maximum Ampere Rating	Catalogue Number	Max. No. 1" Spaces	Max. No. 1/2" Spaces	Cover Style	Dimensions (Inches / mm)			Wire Size Range for Main Cu/Al
					H	W	D	
125	3CBL118	18	36	Flush/Surface	27 / 685.8	14-1/4 / 361.9	3-3/4 / 95.3	#6-300MCM
125	3CBL130	30	60	Flush/Surface	34-1/8 / 866.8	14-1/4 / 361.9	3-3/4 / 95.3	#6-300MCM
125	3CBL142	42	84	Flush/Surface	39 / 990.6	14-1/4 / 361.9	3-3/4 / 95.3	#6-300MCM
225	3CBL218	18	36	Flush/Surface	27 / 685.8	14-1/4 / 361.9	3-3/4 / 95.3	#6-300MCM
225	3CBL230	30	60	Flush/Surface	34-1/8 / 866.8	14-1/4 / 361.9	3-3/4 / 95.3	#6-300MCM
225	3CBL242	42	84	Flush/Surface	39 / 990.6	14-1/4 / 361.9	3-3/4 / 95.3	#6-300MCM



CBL130