
500[®] & 700[®] SERIES RACEWAY




One-piece, single-channel raceway. Easy-to-install and ideal for basic power or communication/low voltage installations. Provides low profile appearance that blends with any decor.

CODE REFERENCE

cULus Listed Raceway: File E4376 Guide RJBT.

Fittings: File E41751 Guide RJPR. Meets Article 386 of NEC. Meets Section 12-1600 of CEC.



KEY

- A. 2089E Reducing Fitting
 B. 504 Mounting Strap
 C. 506 Cover Clip
 D. 511 Flat Elbow
 E. 517 Internal Elbow
 F. 518 External Elbow
 G. 5703 Supporting Clip
- **H.** 5715 Tee
- I. 5719 Corner Box
- J. 5734A Utility Box
- K. 5738 Fixture Box Solid Base
- L. V5739 Fixture Box Solid Base
- M. 5744 Extra Deep Device Box
- N. 5747-2 Two-Gang Shallow
- Device Box 0. 5748S Shallow Device Box
- P. 5748-2 Two-Gang Device Box
- Q. 5748-3 Three-Gang Device Box
- **R.** 5752 Alarm Device Box
- S. 5753 Extra Deep Alarm
- Device Box
- T. 5781 Box Connector
- U. 5782 1/2" Trade Size Conduit Connector
- V. 5785 Combination Connector
- W. V5786 Adjustable Offset Connector
- X. 57240 Single Pole Switch and Box
- Y. 57242 Utility Box
- 2. 57243G Duplex Receptacle and Box

COLOR OPTIONS



 500° and 700° Series Raceway Part Numbers with a "V" prefix have an ivory finish. Part Numbers with a "WH" suffix have a white finish. Some Device Boxes used in safety applications are also available with a red painted finish.


Custom color options are also available. Consult the factory for more information.

24

500[®] & 700[®] SERIES RACEWAY

500 & 700 Series Raceway Fittings Ordering Information (continued)


V5785, 5785WH Combination Connector



Connects raceway, without offsetting, to any surface-mounted 3 1/4" or 4" [83mm or 102mm] outlet box with 1/2" trade size conduit KOs. Base has two 1/2" trade size KOs, one on end and one on bottom. Included spring steel bushing eliminates need


for conduit nipple and locknut for end connection to box. When used with 700 Series Raceway, break off cover extension.

V5786, 5786WH Adjustable Offset Connector



Eliminates need to offset raceway when connecting to surface type panel boxes. Adjustment from surface to center of bushings is 5/8" [15.9mm] minimum to 1 3/8" [35mm] maximum. When used as adjustable offset connector, break out metal between the two holes. When used with 700 Series Raceway, break out crescent twistout in cover. 1/2" trade size chase nipple and locknut furnished.

5790B Armored Cable Connector (Galvanized)



Connects 14/2, 14/3, 12/2, and 12/3 "MC" and armored cable to Wiremold fittings. A short piece of 500 or 700 Series Raceway (1 5/8" [41mm] min.) must be used between connector and Wiremold fittings. Not for use with 1/2" [12.7mm] flex conduit.


5791 EMT Connector



Connects 1/2" trade size EMT to 5700 Series rectangular and round device boxes (except 5733). Derates the fill capacity of the EMT.


500 & 700 Series Raceways Device Boxes Ordering Information

V5731 Blank Cover



Use with 5733 Outlet Box to convert box into pull or junction box. Has 1/2" trade size KO in center.


V5733 Outlet Box



For devices with mounting screw centers of 1 15/32", 1 5/8", 1 11/16", or 1 27/32" [37mm, 41mm, 44mm, or 46mm]. Will accept any device that mounts on "G" or "H" type conduit fittings.

NOTE: 500 & 700 Series Raceway Systems Device Boxes that are identified with this symbol are Certified to Canadian Safety Standards for sale in Canada. When ordering these products (this page and the next page), change the "V" color prefix to "VC" or the "WH" color suffix to "WHC" to deNOTE the Canadian versions.


V5735 Distribution Box



Twistouts permit use of three parallel raceway runs on each side. Base has 1/2" and 1" concentric trade size KOs and a 1 13/16" [46mm] x 2 7/8" [73mm] rectangular KO to mount on a one-gang in-wall outlet box. Cover accepts devices with mounting screw

centers of 2 3/4", 3 1/2" or 4 1/16" [70mm, 89mm or 103mm], and canopy fixtures no larger than 4 5/8" [117mm] in diameter. With 5736 Blank Cover, this fitting can be used as junction box, pull box, etc.

V5736, 5736WH Blank Cover



1/2" trade size KO in center. For use with 5735, 5737, 5737A, 5738, 5738AF, 5739, 5739A or 2135 Device Boxes. Converts these boxes into pull or junction boxes or for hanging lightweight pendant fixtures with 1/2" trade size pipe stems.

29