

1

#### Electronic Timer Modules

Front- (top-) mounted timer modules for use with XTRE10B control relays. Can not be combined with top-mount auxiliary contacts, XTCEXF\_.

XTCEXT\_



#### Electronic Timer Modules for XTRE

Voltage	Contact Sequence	Timing Range	For Use with...	Pkg. Qty. <sup>①</sup>	Catalog Number
<b>On-Delay</b>					
24 Vac/Vdc		0.05–1s	XTRE10B_	1	<b>XTCEXTEEC11T</b>
100–130 Vac		0.5–10s			<b>XTCEXTEEC11A</b>
200–240 Vac		15–100s			<b>XTCEXTEEC11B</b>
<b>Off-Delay</b>					
24 Vac/Vdc		0.05–1s	XTRE10B_	1	<b>XTCEXTED1C11T</b>
100–130 Vac					<b>XTCEXTED1C11A</b>
200–240 Vac					<b>XTCEXTED1C11B</b>
24 Vac/Vdc		0.5–10s	XTRE10B_	1	<b>XTCEXTED10C11T</b>
100–130 Vac					<b>XTCEXTED10C11A</b>
200–240 Vac					<b>XTCEXTED10C11B</b>
24 Vac/Vdc		5–100s	XTRE10B_	1	<b>XTCEXTED100C11T</b>
100–130 Vac					<b>XTCEXTED100C11A</b>
200–240 Vac					<b>XTCEXTED100C11B</b>
<b>Star-Delta</b>					
24 Vac/Vdc		1–30s	XTRE10B_	1	<b>XTCEXTEYC20T</b>
100–130 Vac					<b>XTCEXTEYC20A</b>
200–240 Vac					<b>XTCEXTEYC20B</b>
<b>Sealable Shroud</b>					
	Transparent sealable shroud used to protect electronic timer modules from unwanted access.		XTCEXTEE, XTCEXTED, XTCEXTEY	1	<b>XTCEXTESHRD</b>

**Note**

① Orders must be placed in multiples of package quantity listed.

### Electronic Timer Modules

#### Frames B–C Contactors (7–32A) <sup>①</sup>

XTCEXTE\_



Voltage	Contact Sequence	Timing Range	For Use with...	Pkg. Qty. <sup>②</sup>	Catalog Number	
<b>On-Delay</b>						
24 Vac/Vdc	A1	57 65	0.05s–1s	XTCE...B_	1	XTCEXTEEC11T
100–130 Vac	A2	58 66	0.5s–10s	XTCE...C_	1	XTCEXTEEC11A
200–240 Vac			5s–100s		1	XTCEXTEEC11B
<b>Off-Delay</b>						
24 Vac/Vdc	A1	57 65	0.05s–1s	XTCE...B_	1	XTCEXTED1C11T
100–130 Vac	A2	58 66		XTCE...C_	1	XTCEXTED1C11A
200–230 Vac					1	XTCEXTED1C11B
24 Vac/Vdc	A1	57 65	0.5s–10s	XTCE...B_	1	XTCEXTED10C11T
100–130 Vac	A2	58 66		XTCE...C_	1	XTCEXTED10C11A
200–240 Vac					1	XTCEXTED10C11B
24 Vac/Vdc	A1	57 65	5s–100s	XTCE...B_	1	XTCEXTED100C11T
100–130 Vac	A2	58 66		XTCE...C_	1	XTCEXTED100C11A
200–240 Vac					1	XTCEXTED100C11B
<b>Star-Delta</b>						
24 Vac/Vdc	A1	57 67	1s–30s	XTCE...B_	1	XTCEXTEYC20T
100–130 Vac	A2	58 68		XTCE...C_	1	XTCEXTEYC20A
200–240 Vac					1	XTCEXTEYC20B
<b>Sealable Shroud</b>						
—	Transparent sealable shroud used to protect electronic timer modules from unwanted access		XTCEXTEE, XTCEXTED, XTCEXTEY	1	XTCEXTESHRD	

XTCEXTESHRD



#### Notes

- ① Front (top) mounted timer modules for use with XTCE...B and XTCE...C contactors. Cannot be combined with top-mount auxiliary contacts, XTCEXF...C\_.
- ② Orders must be placed in multiples of package quantity listed.