T&B° Cable Tray

Aluminum Tray

Snap-In Splice Plate

- · Lock into place for easy alignment and installation
- · Packaged in pairs with hardware
- · Standard with each straight and/or fitting



CAT. NO.	MATERIAL	SIDE RAIL HEIGHT
ABW-4-SSP	Aluminum	4"
ABW-5-SSP		5"
ABW-6-SSP		6"
ABW-7-SSP		7"

Snap-In Expansion Splice Plate

- Enables a 1" expansion or contraction of tray system
- · Packaged in pairs with zinc-plated hardware



CAT. NO.	MATERIAL	SIDE RAIL HEIGHT
ABW-4-ESP	Aluminum	4"
ABW-5-ESP		5"
ABW-6-ESP		6"
ABW-7-ESP		7"

Horizontal Adjustable Plate

- Provide maximum installation flexibility
- Furnished in pairs with hardware



CAT. NO.	MATERIAL	FOR TRAY WIDTHS
ABW(*)06HAP		6"
ABW(*)09HAP	Aluminum	9"
ABW(*)12HAP		12"
ABW(*)18HAP		18"
ABW(*)24HAP		24"
ABW(*)30HAP		30"
ABW(*)36HAP		36"
ABW(*)42HAP		42"

(*) Insert side rail height.

Vertical Adjustable Plate

- Provide maximum flexibility for changes in elevation
- · Furnished in pairs with hardware



CAT. NO.	MATERIAL	SIDE RAIL HEIGHT
ABW-4-VSP	Aluminum	4"
ABW-5-VSP		5"
ABW-6-VSP		6"
ABW-7-VSP		7"

T&B aluminum cable tray is composed of two distinct systems — H-Style and U-Style. These systems are interchangeable.

Box to Tray Plates

- Secure tray to electrical panels or boxes, walls or end supports
- Furnished in pairs with hardware



CAT. NO.	MATERIAL	SIDE RAIL HEIGHT
ABW-4-BSP	Aluminum	4"
ABW-5-BSP		5"
ABW-6-BSP		6"
ABW-7-BSP		7"

Closure End Plate

- Provides closure for any tray end
- Includes hardware




CAT. NO.	MATERIAL	SIDE RAIL HEIGHT
ABW-4(*)-CEP		4"
ABW-5(*)-CEP	Aluminum	5"
ABW-6(*)-CEP	Alullillulli	6"
ABW-7(*)-CEP		7"

(*) Insert tray width — 06", 09", 12", 18", 24", 30" or 36".

Reducing Splice Plate

- Used in pairs for a straight reduction
- Use with a standard splice plate for an offset reduction





CAT. NO.	MATERIAL	SIDE RAIL HEIGHT
ABW-4(*)-RSP	Aluminum	4"
ABW-5(*)-RSP		5"
ABW-6(*)-RSP		6"
ABW-7(*)-RSP		7"

(*) For offset reduction: insert width to be reduced.
For straight reduction: insert ½ width to be reduced (two required).
Example: ABW-403-RSP = 3" offset reducer.

Step-Down Splice Plate

- · Connects side rails of different heights
- Hardware included



CAT. NO.	MATERIAL	SIDE RAIL HEIGHT
ABW(*)(**)SDS	Aluminum	4"
		5"
		6"
		7"

(*) Side rail height 1. (**) Side rail height 2. **Note**: Side rail height 1 is greater than side rail height 2.



Tel: 888.862.3289

