

14002

Specifications

Description: Barrier terminal block.

Poles: 2- to 6-poles.

Wire range: 2 – 14 AWG Cu/8 AWG Al.

Ratings:

Volts: — 600Vac/dc

Amps: — 115A

SCCR: — 10kA per
UL 508A table SB4.1

Agency information: CE, Guide XCFR2, UL E62622;
CSA 47235.

Torque ratings*: 2-3, 50 lb-in; 4-6, 45 lb-in; 8, 40 lb-in;
10-14, 35 lb-in.

*Consult factory for torque ratings for CP and Q options.

Marking: Marking strip optional, consult factory.



Catalog numbers

Catalog numbers	Poles	Catalog numbers	Poles
14002-2	2	14002-5	5
14002-3	3	14002-6	6
14002-4	4		

14004

Specifications

Description: Dead front terminal block.

Poles: 2- to 12-poles.

Wire range:
4 – 14 AWG Cu/
8 AWG Al.

Ratings:

Volts: — 600Vac/dc

Amps: — 90A

SCCR: — 10kA per UL 508A table SB4.1

Agency information: CE, Guide XCFR2, UL E62622;
CSA 47235.

Marking: Marking strip optional, consult factory.



Catalog numbers

Catalog numbers	Poles	Catalog numbers	Poles
14004-2	2	14004-8	8
14004-3	3	14004-9	9
14004-4	4	14004-10	10
14004-5	5	14004-11	11
14004-6	6	14004-12	12
14004-7	7		