

Button and Wall Mount Thermal Photocontrols

K4000 Series

These photocontrols install within lighting fixtures, post lamps, or in-wall boxes to provide dusk-to-dawn ON/OFF control of outdoor lighting.

Features

- Mechanical bimetal switch with Cadmium Sulfide photocell
- Compact size fits into standard outlet box, post lamp, wall pack and other lighting fixtures
- Delay feature prevents unwanted OFF switching
- $\frac{3}{8}$ "-18 NPSM, $\frac{3}{4}$ " long stem with locking nut and washer gasket
- K4321C includes weatherproof wall plate and neoprene gasket

Model #	Style	Voltage	Tungsten	Magnetic Ballast
K4021C	Button	120 V	1800 W	1000 VA
K4023C		208-277 V	3100-4150 W	1700-2300 VA
K4027*		347 V	5205 W	2880 VA
K4035†		480 V	7200 W	4000 VA
K4321C	In-Wall	120 V	1800 W	1000 VA


Note: *K4027 is only CSA. †K4035 is not UL/CSA certified.

Accessories

Light Shield	6LV1352
Wall Plate Kit	K43-WP-KIT



6LV1352



K43-WP-KIT



K4021C



K4321C



Ratings	
Operating Voltage	120/208-277/347/480 VAC, 50/60 Hz
Inductive Ballast	8.3 A
Incandescent	15 A
Activation	1 to 5 fc ON, 3 to 15 fc OFF
Operating Temperature	-40° F to 158° F (-40° C to 70° C)
Wire Leads	#18 AWG, 9" L
Dimensions H x W x D	1 $\frac{13}{16}$ " x $\frac{15}{16}$ " x $\frac{13}{16}$ " (46 mm x 23.8 mm x 20.6 mm)
Warranty	2-year limited

Screw-In Lamp Photocontrol

NE1C

This photocontrol screws into a standard light socket to provide quick installation of dusk-to-dawn photocontrol to any lamp fixture.

Features

- For interior or external lights
- ON at dusk, OFF at dawn
- Accommodates any incandescent light up to 150 W

Model #	Style
NE1C	Lamp Screw-In



NE1C



Ratings	
Operating Voltage	120 VAC, 60 Hz
Incandescent	150 W
Activation	1 to 5 fc ON, 3 to 15 fc OFF
Operating Temperature	-40° F to 158° F (-40° C to 70° C)
Warranty	1-year limited