

Construction grade receptacles

Combines safe, rugged, reliable performance with ease-of-installation


Arrow Hart construction grade receptacles are designed to provide a dependable, long lasting user experience while increasing the speed and efficiency of installation

Construction grade 5262 & 5362 series features & benefits

Automatic grounding system eliminates need for bonding jumper in grounded metal enclosures

Nylon face resists high impact and chemical abuse

Patented screw catch captures wallplate screw eliminating hand threading of screw, lost screws and cross-threading



Extra long/wide mounting strap maintains assembly security and helps reach oversize cutouts

0.031" thick triple wipe brass line contacts minimize heat rise and maximize plug retention

Additional features & benefits

- Available in 15A & 20A duplex configurations, including tamper resistant and ArrowLink modular styles
- Convenient built-in #10 and #12 AWG wire strippers
- Tri-combo head terminal and mounting screws

Compliances, specifications and availability are subject to change without notice.

www.eaton.com
www.eaton.com/arrowhart

Straight blade power devices - 20, 30, 50 & 60A



Rating: Amps V/AC	Receptacle/ plug NEMA configuration	Flush receptacles	Wallplates	Surface receptacles	Panel mount receptacles	Plugs	Angle plugs	Connectors	Flanged inlets	Adapters
-------------------------	---	----------------------	------------	------------------------	----------------------------	-------	-------------	------------	-------------------	----------

2-pole, 3-wire grounding

30A 125V	 5-30R	 5-30P	Commercial: 1233 (Brown) Industrial: 5716N (Black)	Standard size: 39CH, 68, 2068, 2168, 93221, 93227 Mid-size: 5068, PJ703, PJ724		Industrial: 5717N (Gray)	Commercial: S41 (Black) Industrial: 5717AN (Gray)	Industrial: 6716N (Gray & Black)	Industrial: 5717NFI (Gray)	
30A 125V	 TT-30R	 TT-30P	Commercial: 1263 (Black)			Commercial: U1263 (Black)		Commercial: 83 (Black)		Commercial: 1264 (Receptacle to NEMA 5-15/5-20 plug) (Black)
30A 250V	 6-30R	 6-30P	Commercial: 1234 (Black) Industrial: 5700N (Black)			Commercial: 1232 (Black)	Industrial: 5701N (Gray)	Commercial: S42 (Black) Industrial: 5701AN (Gray)	Industrial: 6700N (Gray & Black)	Industrial: 5701NFI (Gray)
30A 277V	 7-30R	 7-30P	Industrial: 5795N (Black)				Industrial: 5703N (Gray)	Industrial: 5703AN (Gray)	Industrial: 6795N (Gray & Black)	Industrial: 5703NFI (Gray)
50A 125V	 5-50R	 5-50P	Commercial: 1253 (Black)			Commercial: 1251 (Black)	Industrial: 5712N (Gray)	Commercial: S41 (Black) Industrial: 5712AN (Gray)	Industrial: 6711N (Gray & Black)	Industrial: 5712NFI (Gray)
50A 250V	 6-50R	 6-50P	Commercial: 1254 (Black) Industrial: 5709N (Black)			Commercial: 1252 (Black)	Industrial: 5710N (Gray)	Commercial: S42 (Black) Industrial: 5710AN (Gray)	Industrial: 6709N (Gray & Black)	Industrial: 5710NFI (Gray)
50A 277V	 7-50R	 7-50P					Industrial: 5705N (Gray)	Industrial: 5705AN (Gray)	Industrial: 6796N (Gray & Black)	Industrial: 5705NFI (Gray)

3-pole, 3-wire non-grounding

20A 125/250V	 10-20R	 10-20P	Commercial: 805 (Ivory)			Industrial: 9151N (Gray) Commercial: 2836 (Armed PVC) (Yellow)				
30A 125/250V dryer	 10-30R	 10-30P	Commercial: 38B (Brown)	Standard size: 39CH, 68, 2068, 2168, 93221, 93227	Commercial: 125 (Black)	Industrial: 9337N (Gray)	Commercial: S80 (Black) Industrial: 9352AN (Gray)	Industrial: 9341N (Gray & Black)	Industrial: 9337NFI (Gray)	
50A 125/250V range	 10-50R	 10-50P	Commercial: 32B (Brown) Industrial: 7985N (Black)	Mid-size: 5068, PJ703, PJ724 Standard Size: 192	Commercial: 112 (Black)	Industrial: 4524N (Gray)	Commercial: S80 (Black) Industrial: 7952AN (Gray)	Industrial: 4526N (Gray & Black)	Industrial: 4524NFI (Gray)	

Power device dimensional information: B-20; Specification information: B-25-B-27
Compliances, specifications and availability are subject to change without notice.

All products on this page are RoHS compliant - Page Q-32