



3VL IEC Rated Molded Case Circuit Breakers

Accessories and spare parts

Switch-gears	Rotary operating mechanisms	Size	Cross-section of the actuating shaft	Version ³⁾	Individual parts for 8UC7 door-coupling rotary operating mechanisms	Weight per PU approx.
Type	Type	mm × mm			Order No.	kg
Individual parts for 8UC door-coupling rotary operating mechanisms						
Handles with masking plate (including flat gasket and fixing screws)						
 8UC71101BB	3VL1, 3VL2, 3VL3	8UC71 1	6 × 6 or 8 × 8	Standard EMER- GENCY- STOP	8UC71106BD 8UC71208BD	0.200 0.200
 8UC72106BD	3VL4, 3VL5, 3VL6	8UC72 2	8 × 8	Standard EMER- GENCY- STOP	8UC72106BD 8UC72208BD	0.200 0.200
 8UC73101BB	3VL7, 3VL8	8UC73 3	12 × 12	Standard EMER- GENCY- STOP	8UC73106BD 8UC73208BD	0.200 0.200
Individual parts for 8UC door-coupling rotary operating mechanisms						
Rotary operating mechanisms				Cross-section of the actuating shaft	Individual parts for 8UC6 door-coupling rotary operating mechanisms	Weight per PU approx.
Type				mm × mm	Order No.	kg
Individual parts for 8UC door-coupling rotary operating mechanisms						
Coupling drivers for 3VL						
 8UC6014	8UC71 (plastic) 8UC71/8UC72 ²⁾ (die cast) 8UC73/74 (die cast)		6 × 6 8 × 8 12 × 12		8UC70112AA 8UC60172AA 8UC6014	0.200 0.047 0.253
Extension shafts 300 mm long						
 8UC6031	8UC71 8UC71/8UC72 8UC73 8UC73/74		6 × 6 8 × 8 10 × 10 12 × 12		8UC6031 8UC6032 8UC6033 8UC6034	0.068 0.132 0.217 0.315
Extension shafts 600 mm long						
 8UC6081	8UC71 8UC71/8UC72 8UC73 8UC73/74		6 × 6 8 × 8 10 × 10 12 × 12		8UC6081 8UC6082 8UC6083 8UC6084	0.136 0.265 0.430 0.640
Shaft couplings						
 8UC6021 to 8UC6024	8UC71 8UC72 8UC73 8UC73/74		6 × 6 8 × 8 10 × 10 12 × 12		8UC6021 8UC6022 8UC6023 8UC6024	0.031 0.023 0.085 0.077
Reducers						
 8UC7058	8UC71 8UC72		8 × 8 to 6 × 6 12 × 12 to 8 × 8		8UC7058 8UC7050	0.200 0.200

¹⁾ Non-interchangeability features.

²⁾ Shortened coupling driver with reduced tolerance compensation.

³⁾ Standard: Ti-grey handle, light-gray masking plate;
EMERGENCY-STOP: Red handle, yellow masking plate.