

SIRIUS 3SE5, 3SE2 mechanical safety switches







With separate actuator

3SE2, plastic enclosures
Enclosure width 52 mm

Selection and ordering data

Complete units

1 or 3 contacts · 3 directions of approach · Degree of protection IP67

Version	Operation	DT	Complete units	
			Article No. <input type="checkbox"/>	
Molded-plastic enclosures in special width of 52 mm				
 <p>3SE2243</p>	Lateral and front-end actuation¹⁾		6 mm stroke	
	<ul style="list-style-type: none"> • With M20 × 1.5 connecting thread - Slow-action contacts 1 NO + 2 NC 	Holding force 5 N	⊙ ▶	3SE2243-0XX40
		Holding force 30 N	⊙ ▶	3SE2243-0XX
		With automatic ejection	⊙ ▶	3SE2243-0XX30
	<ul style="list-style-type: none"> - Slow-action contacts 1 NC 	Holding force 5 N	⊙ ▶	3SE2257-6XX40
		Holding force 30 N	⊙ ▶	3SE2257-6XX
		With automatic ejection	⊙ B	3SE2257-6XX30
	<ul style="list-style-type: none"> • With M16 × 1.5 connecting thread - Slow-action contacts 1 NO + 2 NC - Slow-action contacts 1 NC 	Holding force 5 N	⊙ B	3SE2243-0XX48
		Holding force 30 N	⊙ A	3SE2243-0XX18
		With automatic ejection	⊙ C	3SE2243-0XX38
Holding force 5 N		⊙ B	3SE2257-6XX48	
Holding force 30 N		⊙ C	3SE2257-6XX18	
With automatic ejection		⊙ C	3SE2257-6XX38	
Accessories				
 <p>3SX3218</p>  <p>3SX3228</p>  <p>3SX3256</p>  <p>3SX3217</p>  <p>3SX3234</p>	Actuators			
	<ul style="list-style-type: none"> • Standard actuators ($r_{\min} = 150$ mm), length 28 mm 	A	3SX3218	
	<ul style="list-style-type: none"> • Universal radius actuator ($r_{\min} = 45$ mm), length 34 mm 	A	3SX3228	
	<ul style="list-style-type: none"> • Radius actuator, adjustable radius, length 34 mm 	D	3SX3256	
	<ul style="list-style-type: none"> • Ball locating, force adjustable up to 100 N by 2 screws, length 28 mm 	A	3SX3217	
<ul style="list-style-type: none"> • Actuator, length 34 mm, with dust protection and slit cover 	D	3SX3234		
Accessories				
<ul style="list-style-type: none"> • Slit cover (1 set = 3 units) 	D	3SX3233		

⊙ Positive opening according to IEC 60947-5-1, Appendix K.

¹⁾ Supplied without actuator.