


## Ground Rod Clamps

A dependable ground connection offered at a substantial savings.

### Type G — Budget-Line Ground Clamps

- Cast of high-strength corrosion-resistant copper alloy
- Furnished with hex head bolts
- Simplified, compact design makes lasting, trouble-free connection
- UL® Listed for direct burial





CAT. NO.	NOMINAL ROD DIA.		WIRE RANGE				DIMENSIONS (IN.)					
	(IN.)	(MM)	MAX.	MIN.	MAX. (MM²)	MIN. (MM²)	A (MAX.) BOLT	SCREW THREAD SIZE UNC-2A	B	C	D	E
G3*	3/8	9.5	4 Str.	10 Sol.	21.1	5.2	1 1/8	5/16-18	1 1/16	1/2	27/64	3/8
G4	1/2	12.7	2 Str.	10 Sol.	33.6	5.2	—	3/8-16	27/32	3/8	37/64	1/2
G5‡	5/8	15.8	2 Str.	10 Sol.	33.6	5.2	—	3/8-16	29/32	3/8	43/64	1/2
G6	3/4	19.0	2 Str.	10 Sol.	33.6	5.2	—	3/8-16	1 1/16	3/8	13/16	1/2

\* Not UL Listed.  
 ‡ RUS Accepted.  
 Add suffix P to Cat. No. for tin-plated clamp.

Axial groove keeps wire and rod in perfect alignment.

### Types GG and GGH — Heavy-Duty Ground Rod Clamps

- Cast of high-strength corrosion-resistant copper alloy
- Both hex head bolts and socket set screws available
- Floating pressure bar distributes pressure evenly over large area of ground wire



CAT. NO.*		NOMINAL ROD DIA.		WIRE RANGE				DIMENSIONS (IN.)				
SOCKET SET SCREW	HEX HEAD BOLT	(IN.)	(MM)	MAX.	MIN.	MAX. (MM²)	MIN. (MM²)	A (MAX.) SOCKET SCREW	A (MAX.) HEX BOLT	SCREW THREAD SIZE UNC-2A	B	C
GG12	GG12H	1/2	12.7	2 Str.	8 Sol.	33.6	8.3	1 13/64	1 13/16	7/16-14	27/32	15/16
GG58	GG58H	5/8	15.8	2 Str.	8 Sol.	53.6	8.3	1 51/64	2 1/32	7/16-14	61/64	15/16
—	GG34H	3/4	19.0	4/0 Str.	8 Sol.	120.6	8.3	—	3	1/2-14	1 3/8	1 1/4

\* Add suffix P to Cat. No. for tin-plated clamp.  
 GG34H has no pressure bar or axial groove.