

Non-Shielded Cable

3M™ Cold Shrink Termination Kits 5610-A Series for 5 & 8 kV Non-Shielded Cables

3M™ Cold Shrink Termination Kits 5610-A series provide an environmental seal to the terminal lug area of 5–8 kV unshielded power cable. Each kit contains material needed to seal three cable ends. Terminal lug must be ordered separately. Kits can be used for both indoor (protected) and outdoor (weather-exposed) applications.

The silicone rubber provides tracking protection for the lug ends of the cable.

Number of Conductors	Single Conductor
Shielding Type	Non-Shielded
Indoor/Outdoor	Both
Breakout Boot	No
Insulation Rejacketing	No
No. Skirts	0
Voltage	5 kV, 8 kV
Packaging	1 kit per case



Order No.	UPC	Max. Installed Length	Cable Insulation O.D.	Conductor Size 5 kV & 8 kV
5611A	054007-49549	7.5" (191 mm)	0.31"-0.72" (7,9-18,3 mm)	8-4 AWG (10-16 mm ²)
5612A	054007-49550	8.0" (203 mm)	0.44"-0.95" (11,2-24,1 mm)	2-2/0 AWG (35-60 mm ²)
5613A	054007-49551	8.0" (203 mm)	0.56"-1.18" (14,2-30,0 mm)	3/0 AWG-300 kcmil (95-150 mm ²)
5614A	054007-49552	8.0" (203 mm)	0.95"-1.94" (24,1-49,3 mm)	350-1000 kcmil (185-500 mm ²)