

# Locking Devices

## Weather Protective Boots; 72002 Series



- Help prevent moisture, dust and other contaminants from infiltrating plugs and connectors
- Chemical/UV-resistant construction
- Available in high visibility yellow or standard black
- Ribbed exterior provides firm grip
- Sealing ring seals connector when not mated
- For use with Bryant Triple Gripper® 20 and 30 amp nylon plugs and connectors



**72002BP**



**72002BC with  
72002BSR**



**7716B**



**7717B**

### WEATHER PROTECTIVE BOOTS

Description	Catalog Number
Black neoprene boot for use with 20 and 30 amp nylon locking plugs	<b>72002BPB</b>
Yellow neoprene boot for use with 20 and 30 amp nylon locking plugs	<b>72002BP</b>
Black neoprene boot for use with 20 and 30 amp nylon locking connectors	<b>72002BCB</b>
Yellow neoprene boot for use with 20 and 30 amp nylon locking connectors	<b>72002BC</b>
Black neoprene sealing cap seals connector	<b>72002BSRB</b>
Yellow neoprene sealing cap seals connector	<b>72002BSR</b>
Black elastomer weather protective boot for 50 amp plugs when used in a cord set and connectors when used with flanged inlets	<b>7716B</b>
Black elastomer weather protective boot for 50 amp connectors when used in a cord set	<b>7717B</b>



SS7

### 20 AMP ACCESSORIES RECEPTACLE PLATES Inches (mm)

Description	Catalog Number
Stainless steel; type 302/304; single-gang; 1.40 in. (35.6) opening	SS7
Brass; single-gang; 1.40 in. (35.6) opening	SB7
Black nylon; single-gang; 1.40 in. (35.6) opening	NP7BK
Cast aluminum; with lift cover; indoor use; box mount	23007
Weather protective cast aluminum; with cover; F.S. box mount	7418B



23007

### 30 AMP ACCESSORIES LIQUID-TIGHT METALLIC CONDUIT ADAPTERS

Description	Catalog Number
For use with plug and connector with 1/2 in. conduit	SAB12A*
For use with plug and connector with 3/4 in. conduit	SAB34A*

Note: \*Not CSA Certified.



SAB34A

### "MINI" WEATHER PROTECTIVE BOOTS

Description	Catalog Number
Mini boot for use with female connector	20424**
Mini boot for use with male plug	20425**

Note: Boots are not available for 5-wire 30 amp power interrupting plugs and connectors.

\*\*Not UL Listed or CSA Certified.

### RECEPTACLE PLATES

Description	Catalog Number
Weather protective plate; cast aluminum for wet locations with cover closed	20405
Cast aluminum; no lift cover	20406

Note: \*Not CSA Certified.



20424



20425

### 60 AMP SINGLE RECEPTACLE ACCESSORIES BOX AND ADAPTERS (BOX REQUIRES ONE ADAPTER)

Description	Catalog Number
Box; cast aluminum	26401
Straight adapter plate; cast aluminum	26402
45° angle adapter; cast aluminum	26404



26401



26402



26404

### PRODUCT DIMENSIONS Inches (mm)

