




## 2 Pole 3 Wire Grounding 15 Amp 125V; 20 Amp 125V Commercial Grade Receptacles




CR15-BI



CR15-BI side



CR20-BI



CR20-BI side

### Features - Specifications

- Full-face, wraparound design is molded of high-impact, chemical-resistant nylon
- Heavy-duty wraparound steel yoke
- Terminal screws: brass combination Phillips/slotted binding head accepts up to #10 wire
- Back wiring: eight wiring pockets for convenient feed-thru wiring, clamp-type terminals accepts up to #10 wire
- Approved for CU wire only
- Large green, combination Phillips/slotted hex head backed out and staked for easy wiring
- Self-grounding strap for fast installations
- Easily accessible break-off tab for two-circuit wiring
- One-piece triple-wipe brass line contacts
- Double-wipe brass grounding contacts
- UL Listed File #E2258 – Guide #RTRT
- CSA Certified File #LR16215 – Guide #365E1
- Complies with NEMA Standards WD-1, WD-6 and UL 498
- NOM

### 15 AMP 125V DUPLEX RECEPTACLES NEMA 5-15

CATALOG NUMBER		DESCRIPTION
SIDE WIRED	BACK & SIDE WIRED	
CR15-B	CBR15-B	Brown nylon face, self-grounding
CR15-BCAN	CBR15-BCAN	Same as above except with Robertson head screws
CR15-BGRY	CBR15-BGRY	Gray nylon face, self-grounding
CR15-BGYCAN	CBR15-BGRYC	Same as above except with Robertson head screws
CR15-BI	CBR15-BI	Ivory nylon face, self-grounding
CR15-BICAN	CBR15-BICAN	Same as above except with Robertson head screws
CR15-BLK	CBR15-BLK	Black nylon face, self-grounding
CR15-BW	CBR15-BW	White nylon face, self-grounding
CR15-BWCAN	CBR15-BWCAN	Same as above except with Robertson head screws

### 20 AMP 125V DUPLEX RECEPTACLES NEMA 5-20

CATALOG NUMBER		DESCRIPTION
SIDE WIRED	BACK & SIDE WIRED	
CR20-B	CBR20-B	Brown nylon face, self-grounding
CR20-BGRY	CBR20-BGRY	Gray nylon face, self-grounding
CR20-BI	CBR20-BI	Ivory nylon face, self-grounding
CR20-BLK	CBR20-BLK	Black nylon face, self-grounding
CR20-BW	CBR20-BW	White nylon face, self-grounding

### PRODUCT DIMENSIONS – ( ) Indicates mm dimensions

