

**12V MAX\***  
**LITHIUM ION**



**Wireless Screen**  
Removable for use in tight areas



**Video & Photo Capture**  
Stores on Micro SD card



**Hook & Magnet Tools**  
Attachments to aid retrieval

**Zoom Capability**  
Up to 3x zoom for increased visibility



12V MAX\*

**INSPECTION CAMERA**

**6CXN6**

**14H387**

**N/A**

**6CXN7**



**DCT410S1**

12V MAX\* 17mm Inspection Camera with Wireless Screen Kit



**DCT411S1**

12V MAX\* 9mm Inspection Camera with Wireless Screen Kit



**DCT412S1**

12V MAX\* 5.5mm Inspection Camera with Wireless Screen Kit



**DCT414S1**

12V MAX\* Infrared Thermometer Kit

SPECS	6CXN6	14H387	N/A
Volts	12V MAX*	12V MAX*	12V MAX*
Camera Head Diameter	17 mm	9 mm	5.5 mm
Camera Cable	3' (waterproof)	3' (waterproof)	3' (waterproof)
Screen Size	3-1/2"	3-1/2"	3-1/2"
Resolution	320 x 480 dpi	320 x 480 dpi	320 x 480 dpi
Zoom	3X	3X	3X
Charger/Batteries	Fast Charger, (1) 12V Max* Lithium Ion Battery	Fast Charger, (1) 12V Max* Lithium Ion Battery	Fast Charger, (1) 12V Max* Lithium Ion Battery
Includes	(1) 3' camera cable, (1) hook & (1) magnet	(1) 3' camera cable, (1) hook, (1) magnet & (1) mirror	(1) 3' camera cable

SPECS	6CXN7
Volts	12V MAX*
Temperature Range	-20° F to 932° F (-29° C to 500° C)
Field of View; Distance: Spot	(D:S) 12:1
Accuracy	+/- 1.5% or +/- 1.5° C, whichever is greater, assumes ambient
Laser Power	<1 mw class II laser product
Charger/Batteries	Fast Charger, (1) 12V Max* Lithium Ion Battery
Includes	-

**ACCESSORIES AVAILABLE**

- DCT4101 / 14H388 – 17mm Camera Cable
- DCT4102 – 9mm Camera Cable
- DCT4103 / 14H389 – 17mm Cable Extension
- DCT4105 – 5.5mm Camera Cable

**All cameras, cables and extensions are interchangeable.**

**ALSO AVAILABLE**



DCL510

**6CXN7 LED WORKLIGHT**

**130 Lumen LED light**  
Provides bright illumination

**Head rotates 360° & pivots**  
Provides light in any direction

**Magnet and belt clip**  
Hands free use in multiple placements

**Kick stand**