

OMNIBOX™ SERIES FLOOR BOXES



OmniBox Series™ Floor Boxes provide an excellent activation solution when multiple services are required in open space areas to meet the workstation needs of today's applications.

CODE REFERENCE

cULus Listed

Metallic Outlet Boxes:

File E2961 Guide QCIT.

Meets Article 314.27(C) of NEC.

COLOR OPTIONS


OmniBox Series™ Flanges Cover Plates are available in the these colors as indicated in the part number descriptions.

Custom color options are also available. Consult the factory for more information.

OMNIBOX™ SERIES FLOOR BOXES


Omnibox Series Brushed Aluminum Cover Plates Ordering Information

828R-TCAL Brushed Aluminum Duplex Cover Plate



Flip lids. Can also be used with a 106 type communication adapter.


830CKTCAL Brushed Aluminum Cover Plate



Power or communication plate with 2" [51mm] and 1 1/4" [32mm] plugs.


NOTE: Acceptable for use with threaded conduit when passing through power cables.

828GFITCAL Brushed Aluminum GFI Cover Plate



May be used with Activate and Ortronics® Connectivity Systems in conjunction with 817B, 827B, and 837B Flanges.


830CKTCAL-1 Brushed Aluminum Cover Plate



Power or communication plate with 2" [51mm] and 1" [25mm] plugs.


NOTE: Acceptable for use with threaded conduit when passing through power cables.

828DPGFITCAL Brushed Aluminum Rectangular Cover Plate



Allows for mounting of a duplex style receptacle with a rectangular style flip lid cover.


830CKTCAL-3/4 Brushed Aluminum Cover Plate



Power or communication plate with 2" [51mm] and 3/4" [19.1mm] plugs.

NOTE: Acceptable for use with threaded conduit when passing through power cables.


828COMTCAL Brushed Aluminum Communication Cover Plate



Allows for up to four communication devices to be mounted in a recessed position within the 880 Floor Box. The 828COMTCAL Cover Plate has removable slides for cable egress.

NOTE: For use with 880S & 880CS Series Boxes only.


830CKTCAL-1/2 Brushed Aluminum Cover Plate



Power or communication plate with 2" [51mm] and 1/2" [12.7mm] plugs.


NOTE: Acceptable for use with threaded conduit when passing through power cables.

828DLRAL Brushed Aluminum Single Locking Receptacle Cover Plate



Single flip lid cover for 20A or 30A single locking receptacles. Device opening is 2 5/8" [67mm]. For use with maximum female locking device of 1.58" diameter, and maximum male plug face of 2.25" diameter.

828MAAP AV Adapter Plate



Sheet metal adapter plate that accepts two (2) Legrand AVIP or Extron® Electronics MAAP style device plates (sold separately). For use with 828GFITC or 828GFITCAL cover plates (sold separately).

NOTE: UL Listed for tile, terrazzo, and carpet floors. Brass covers and flanges are not interchangeable with aluminum or nonmetallic covers and flanges. Nonmetallic covers are interchangeable with aluminum flanges.