



Code Conductor, Two-Hole, Long Barrel with Window Lug (continued)

B1.
Cable
Ties

B2.
Cable
Accessories

B3.
Stainless
Steel Cable
Ties &
Accessories

C1.
Wiring
Duct

C2.
Abrasion
Protection

C3.
Cable
Management

D1.
Terminals

D2.
Power
Connectors

D3.
Grounding
Connectors

E1.
Labeling
Systems

E2.
Labels

E3.
Pre-Printed
&
Write-On
Markers

E4.
Permanent
Identification

E5.
Lockout/
Tagout &
Safety
Solutions

F.
Keystone
Cabling
Systems

G.
Part
Number
Index

Part Number	Figure No.	Copper Conductor Size	Stud Hole Size (In.)	Stud Hole Spacing (In.)	Figure Dimensions (In.)				Panduit Color Code	Panduit Die Index No.‡	Burndy Die Index No.‡	T&B Die Index No.‡	Wire Strip Length (In.)	Std. Pkg. Qty.
					W	B	T	L						
LCC2-56BW-Q	1	#2 AWG	5/16	0.75	0.66	1.16	0.10	2.92	Brown	P33	10	33	1 1/4	25
LCC2-56CW-Q	1		5/16	0.88	0.66	1.16	0.10	3.04	Brown	P33	10	33	1 1/4	25
LCC2-38BW-Q	1		3/8	0.75	0.66	1.16	0.10	2.99	Brown	P33	10	33	1 1/4	25
LCC2-38CW-Q	1		3/8	0.88	0.66	1.16	0.10	3.12	Brown	P33	10	33	1 1/4	25
LCC2-38DW-Q	1		3/8	1.00	0.66	1.16	0.10	3.24	Brown	P33	10	33	1 1/4	25
LCC2-38W-Q	1		3/8	1.75	0.66	1.16	0.10	3.99	Brown	P33	10	33	1 1/4	25
LCC2-12W-Q	1		1/2	1.75	0.75	1.16	0.08	4.41	Brown	P33	10	33	1 1/4	25
LCC1-14AW-E	1	#1 AWG	1/4	0.63	0.70	1.36	0.11	2.89	Green	P37	11	37	1 7/16	20
LCC1-14BW-E	1		1/4	0.75	0.70	1.36	0.11	3.01	Green	P37	11	37	1 7/16	20
LCC1-56BW-E	1		5/16	0.75	0.70	1.36	0.11	3.14	Green	P37	11	37	1 7/16	20
LCC1-56CW-E	1		5/16	0.88	0.70	1.36	0.11	3.26	Green	P37	11	37	1 7/16	20
LCC1-38DW-E	1		3/8	1.00	0.70	1.36	0.11	3.46	Green	P37	11	37	1 7/16	20
LCC1-12W-E	1		1/2	1.75	0.75	1.36	0.09	4.63	Green	P37	11	37	1 7/16	20
LCC1/0-14AW-X	1		1/0 AWG	1/4	0.63	0.76	1.44	0.12	3.07	Pink	P42	12	42	1 1/2
LCC1/0-14BW-X	1	1/4		0.75	0.76	1.44	0.12	3.19	Pink	P42	12	42	1 1/2	10
LCC1/0-14DW-X	1	1/4		1.00	0.76	1.44	0.12	3.44	Pink	P42	12	42	1 1/2	10
LCC1/0-38DW-X	1	3/8		1.00	0.76	1.44	0.12	3.57	Pink	P42	12	42	1 1/2	10
LCC1/0-38W-X	1	3/8		1.75	0.76	1.44	0.12	4.32	Pink	P42	12	42	1 1/2	10
LCC1/0-12DW-X	1	1/2		1.00	0.80	1.44	0.12	3.84	Pink	P42	12	42	1 1/2	10
LCC1/0-12W-X	1	1/2		1.75	0.80	1.44	0.12	4.74	Pink	P42	12	42	1 1/2	10
LCC2/0-14AW-X	1	2/0 AWG	1/4	0.63	0.85	1.50	0.13	3.23	Black	P45	13	45	1 9/16	10
LCC2/0-14BW-X	1		1/4	0.75	0.85	1.50	0.13	3.36	Black	P45	13	45	1 9/16	10
LCC2/0-56DW-X	1		5/16	1.00	0.85	1.50	0.13	3.61	Black	P45	13	45	1 9/16	10
LCC2/0-38DW-X	1		3/8	1.00	0.85	1.50	0.13	3.67	Black	P45	13	45	1 9/16	10
LCC2/0-12DW-X	1		1/2	1.00	0.85	1.50	0.13	3.92	Black	P45	13	45	1 9/16	10
LCC2/0-12W-X	1		1/2	1.75	0.85	1.50	0.13	4.83	Black	P45	13	45	1 9/16	10
LCC3/0-14BW-X	1		3/0 AWG	1/4	0.75	0.96	1.50	0.13	3.39	Orange	P50	14	50	1 9/16
LCC3/0-56DW-X	1	5/16		1.00	0.96	1.50	0.13	3.64	Orange	P50	14	50	1 9/16	10
LCC3/0-38DW-X	1	3/8		1.00	0.96	1.50	0.13	3.70	Orange	P50	14	50	1 9/16	10
LCC3/0-12DW-X	1	1/2		1.00	0.96	1.50	0.13	3.95	Orange	P50	14	50	1 9/16	10
LCC3/0-12W-X	1	1/2		1.75	0.96	1.50	0.13	4.87	Orange	P50	14	50	1 9/16	10
LCC4/0-14AW-X	1	4/0 AWG	1/4	0.63	1.06	1.56	0.14	3.35	Purple	P54	15	54	1 5/8	10
LCC4/0-14BW-X	1		1/4	0.75	1.06	1.56	0.14	3.48	Purple	P54	15	54	1 5/8	10
LCC4/0-56DW-X	1		5/16	1.00	1.06	1.56	0.14	3.74	Purple	P54	15	54	1 5/8	10
LCC4/0-38DW-X	1		3/8	1.00	1.06	1.56	0.14	3.81	Purple	P54	15	54	1 5/8	10
LCC4/0-38W-X	1		3/8	1.75	1.06	1.56	0.14	4.56	Purple	P54	15	54	1 5/8	10
LCC4/0-12DW-X	1		1/2	1.00	1.06	1.56	0.14	4.04	Purple	P54	15	54	1 5/8	10
LCC4/0-12W-X	1		1/2	1.75	1.06	1.56	0.14	4.95	Purple	P54	15	54	1 5/8	10

‡Visit www.panduit.com/tools for tool and die information.

*Not tested to NEBS level 3 requirements.

**Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V.

◆NEMA hole sizes and spacing.

Continues on next page