

7

IEC and British Standard fuses

Class gG IEC 60269 industrial ferrule fuses

8x31mm, Class gG, 400Vac, 0.5 to 20 A

Catalog numbers		Rated voltage (Vac)	Amps	Interrupting rating at rated voltage (kA)
Without indicator	With indicator			
C08G0-5	-	400	0.5	20
C08G1	-		1	
C08G2	C08G2I		2	
C08G4	C08G4I		4	
C08G6	C08G6I		6	
C08G8	C08G8I		8	
C08G10	C08G10I		10	
C08G12	C08G12I		12	
C08G16	C08G16I		16	
C08G20	C08G20I		20	



10x38mm, Class gG, 500 and 400Vac, 0.5 to 32 A

Catalog numbers		Rated voltage (Vac)	Amps	Interrupting rating at rated voltage (kA)	Recommended fuse holder
Without indicator	With indicator				
C10G0-5	-	500	0.5	120	• CHM DIN-Rail* • BMM modular block
C10G1	C10G1I		1		
C10G2	C10G2I		2		
C10G4	C10G4I		4		
C10G6	C10G6I		6		
C10G8	C10G8I		8		
C10G10	C10G10I		10		
C10G12	C10G12I		12		
C10G16	C10G16I		16		
C10G20	C10G20I		20		
C10G25	C10G25I		25		
C10G32	C10G32I	400	32		
C10G32	-	400	32		
-	C10G32I	500	32		
-	C10G40I	500	40		
-	C10G50I	400	50		



* Not recommended for use with indicator version.

14x51mm, Class gG, 400, 500 and 690Vac, 1 to 50 A

Catalog numbers			Rated voltage (Vac)	Amps	Interrupting rating at rated voltage (kA)	Recommended fuse holder
Without indicator	With indicator	With striker				
C14G1	C14G1I	-	690	1	80	• CH14 DIN-Rail**
C14G2	C14G2I	-		2	120	
-	-	C14G2S	500	4	80	
C14G4	C14G4I	-	690		120	
-	-	C14G4S	500	6	80	
C14G6	C14G6I	-	690		120	
-	-	C14G6S	500	8	80	
C14G8	C14G8I	-	690		120	
-	-	C14G8S	500	10	80	
C14G10	C14G10I	-	690		120	
-	-	C14G10S	500	12	80	
C14G12	C14G12I	-	690		120	
-	-	C14G12S	500	16	80	
C14G16	C14G16I	-	690		120	
-	-	C14G16S	500	20	80	
C14G20	C14G20I	-	690		120	
-	-	C14G20S	500	25	80	
C14G25	C14G25I	-	690		120	
-	-	C14G25S	500	32	120	
C14G32	C14G32I	C14G32S				40
C14G40	C14G40I	C14G40S				
C14G50	C14G50I	C14G50S	400	50		



** Not recommended for use with indicator version, use striker version to acutate optional, external microswitch.

Data Sheet 720115