

Intended Use

An affordable digital lighting platform designed to deliver general ambient lighting for recessed-ceiling applications in schools, offices and hospitals. Built on the tried-and-true GT troffer platform, the LED technology ensures reliable color consistency and extended service life of at least 50,000 hours.

Features

- 2'x2' GTL LED replaces 2- to 4-lamp T8; 2'x4' GTL LED replaces 2-lamp T8
- 2'x2' and 2'x4' configurations

- 3700 and 4000 lumen packages
- 3500 and 4000K CCTs
- Excellent lumen maintenance - L70 50,000 hrs
- Frosted pattern A12 lens

Listings

CSA Certified to meet U.S. and Canadian safety standards. DesignLights Consortium® qualified product. Tested to LM80 standards. Damp location listed.

LED TROFFERS

2'x2', 2'x4'



CONTRACTOR
SELECT

ORDERING INFORMATION

Specifications subject to change.

Example: 2GTL4 LP835

Catalog Number	Description	Lumens	Color temperature	Lens type	Voltage
2GTL2 LP835	2x2 LED Recessed Troffer	3700 Lumens	3500K	Patterned #12 acrylic	120-277
2GTL2 LP840	2x2 LED Recessed Troffer	3700 Lumens	4000K	Patterned #12 acrylic	120-277
2GTL4 LP835	2x4 LED Recessed Troffer	4000 Lumens	3500K	Patterned #12 acrylic	120-277
2GTL4 LP840	2x4 LED Recessed Troffer	4000 Lumens	4000K	Patterned #12 acrylic	120-277
2GTL4 347 LP835	2x4 LED Recessed Troffer	4000 Lumens	3500K	Patterned #12 acrylic	347
2GTL4 347 LP840	2x4 LED Recessed Troffer	4000 Lumens	4000K	Patterned #12 acrylic	347
2GTL2 347 LP835	2x2 LED Recessed Troffer	3700 Lumens	3500K	Patterned #12 acrylic	347
2GTL2 347 LP840	2x2 LED Recessed Troffer	3700 Lumens	4000K	Patterned #12 acrylic	347


ADDITIONAL INFORMATION

For additional product information, visit www.lithonia.com.

Drawings are for dimensional detail only and may not represent actual mechanical configuration. Dimensions are shown in inches (centimeters) unless otherwise noted.

Specifications

- Length: 24 (61.0) for 2' x 2'
48 (122.0) for 2' x 4'
- Width: 24 (61.0)
- Depth: 3-1/4 (8.2)



ACCESSORIES

ORDER SEPARATELY

- DGA22 Drywall grid adapter for 2x2 recessed fixture
- DGA24 Drywall grid adapter for 2x4 recessed fixture

Certain airborne contaminants can diminish integrity of acrylic and polycarbonate. Refer to the Acrylic & Polycarbonate Environmental Compatibility tables on pages 1116-1117 for suitable uses.