
500® & 700® SERIES RACEWAY




One-piece, single-channel raceway. Easy-to-install and ideal for basic power or communication/low voltage installations. Provides low profile appearance that blends with any decor.

CODE REFERENCE

cULus Listed Raceway: File E4376 Guide RJBT.

Fittings:

File E41751 Guide RJPR. Meets Article 386 of NEC. Meets Section 12-1600 of CEC.



KEY

- A. 2089E Reducing Fitting
- **B.** 504 Mounting Strap
- C. 506 Cover Clip
- D. 511 Flat Elbow
- E. 517 Internal Elbow
- F. 518 External Elbow
- G. 5703 Supporting Clip
- **H.** 5715 Tee

- I. 5719 Corner Box
- J. 5734A Utility Box
- K. 5738 Fixture Box Solid Base
- L. V5739 Fixture Box Solid Base
- M. 5744 Extra Deep Device Box
- N. 5747-2 Two-Gang Shallow Device Box
- 0. 5748S Shallow Device Box
- P. 5748-2 Two-Gang Device Box
- Q. 5748-3 Three-Gang Device Box
- R. 5752 Alarm Device Box
- **S.** 5753 Extra Deep Alarm Device Box
- T. 5781 Box Connector
- U. 5782 1/2" Trade Size Conduit Connector
- V. 5785 Combination Connector
- W. V5786 Adjustable Offset Connector
- X. 57240 Single Pole Switch and Box
- Y. 57242 Utility Box
- Z. 57243G Duplex Receptacle and Box

COLOR OPTIONS



500° and 700° Series Raceway Part Numbers with a "V" prefix have an ivory finish. Part Numbers with a "WH" suffix have a white finish. Some Device Boxes used in safety applications are also available with a red painted finish.

Custom color options are also available. Consult the factory for more information.



500® & 700® SERIES RACEWAY

500 Series Wire Fill Capacities For Communications

	CABLE/WIRE SIZE	O.D. (APPRO Inches	X. DIA.) [mm]	40% FILL
UNSHIELDED TWISTED PAIR	4-pair, 24 AWG, Cat 3	0.190	[4.8]	2
	4-pair, 24 AWG, Cat 5e	0.210	(5.3)	2
	4-pair, 24 AWG, Cat 6	0.250	(6.3)	1
	4-pair, 24 AWG, Cat 6a*	0.354	(9.0)	0
	25-pair, 24 AWG	0.410	(10.4)	0
COAXIAL	RG6/U	0.270	[6.9]	1
FIBER	ZipCord	0.118 x 0.236	[3 x 6]	2
	Round 4 Strand Fiber	0.187	[4.8]	2
	Round 6 Strand Fiber	0.256	[6.5]	1


500 Series Raceway Ordering Information

V500 One-Piece Raceway



.040" [1.0mm] steel. Ivory finish. Available in 10' [3m] lengths, 100' [31m] per carton. One (1) 5701 Coupling furnished with each length.

V500-5 One-Piece Raceway



Same as V500 Raceway except in 5' [1.5m] lengths, 50' [15m] per carton. One (1) 5701 Coupling furnished with each 5' [1.5m] length.

605 500 Series Raceway Cutter



Single action portable cutter. Fast and easy square cuts.

605K Replacement Blades

Case hard steel replacement blades for 605 Raceway Cutter.

502 Bushing



Protects wires from abrasion. Slips into open end of 500 Series Raceway.

V504 Mounting Strap



(One- or Two-Hole) – Converts to one-hole by breaking off at score. Lanced tab holds strap in place while fastening to surface.

NOTE: Use #8 flathead screws with all fittings requiring screws except V504. With V504, use #8 panhead screws.

500 Series Wire Fill Capacities for Power

WIRE SIZE	0.D.		NO. OF CONDUCTORS	
THHN/THWN	Inches	[mm]	40% FILL	
14 AWG	0.111	[2.8]	7	
12 AWG	0.130	[3.3]	5	
10 AWG	0.164	[4.2]	3	

NOTE: For additional information, refer to the Technical Section.

* Category 6 augmented (6a) cable for 10 gigabit ethernet – max allowed cable diameter per addenda No. 11 ANSI TIA/EIA 568-B.2.

V506 Connection Cover



Covers seam where two lengths of 500 Series Raceway come together.

V511 Flat Elbow



Right angle turns on the same surface.

V512 45° Flat Elbow



Diagonal 45° turns on same surface.

V517 Internal Elbow



Inside right angle turns.

V518 Outside Elbow



Outside right angle turns.

5700LL Laser Level



For 500/700 Series Raceway. Attaches to outlet box base and raceway fittings for perfect alignment of runs of raceway.

5700CG Cutting Guide



For 500/700 Series Raceway. Attaches to step ladder and holds raceway channel securely for accurate cuts.