

### Renewal Parts

#### Renewal Contact Kits for C25 Definite Purpose Contactors

- Replace complete contactor for:
  - C25A\_
  - C25B\_
  - C25C\_
  - C25D\_

#### Renewal Contact Kits for C25 Definite Purpose Contactors

| Catalog Number | Single-Pole Kit Part Number | Two-Pole Kit Part Number | Three-Pole Kit Part Number |
|----------------|-----------------------------|--------------------------|----------------------------|
| C25FNF250      | —                           | 6-65-5                   | —                          |
| C25FNF350      | —                           | —                        | 6-65-6                     |
| C25FNF260      | —                           | 6-65-7                   | —                          |
| C25FNF360      | —                           | —                        | 6-65-8                     |
| C25FNF275      | —                           | 6-65-20                  | —                          |
| C25FNF375      | —                           | —                        | 6-65-19                    |
| C25GNF290      | —                           | —                        | —                          |
| C25GNF390      | —                           | —                        | —                          |
| C25HNE3120     | —                           | —                        | 6-43-6                     |
| C25KNE3200     | —                           | —                        | 6-288                      |
| C25KNE3300     | —                           | —                        | 6-286                      |
| C25LNE3360     | —                           | —                        | 6-45-2                     |

### Product Selection

#### AC Coils

| AC Coil Voltage  | Frequency | Inrush (Maximum) |       | Sealed (Maximum) |       | Coil Suffix | Class          | Part Number      |
|--|-----------|------------------|-------|------------------|-------|-------------|----------------|------------------|
|  |           | VA               | Watts | VA               | Watts |             |                |                  |
| <b>15, 25, 30 and 40A – Two- and Three-Pole (Series D1 and E1)</b> |           |                  |       |                  |       |             |                |                  |
| 12   | 60        | 74.85            | 46.1  | 5.53             | 1.68  | <b>R</b>    | Class F, 155°C | <b>9-3185-5</b>  |
| 24   |           | 81.35            | 49.7  | 5.83             | 1.74  | <b>T</b>    |                | <b>9-3185-6</b>  |
| 110/120  |           | 74.69            | 51.6  | 5.79             | 1.81  | <b>A</b>    |                | <b>9-3185-1</b>  |
| 208/240  |           | 82.64            | 59.1  | 6.96             | 2.38  | <b>B</b>    |                | <b>9-3185-2</b>  |
| 220/240  | 60        | 74.03            | 51.8  | 5.85             | 1.99  | <b>J</b>    | Class F, 155°C | <b>9-3185-10</b> |
| 440/480  |           | 73.39            | 52.1  | 6.09             | 2.58  | <b>C</b>    |                | <b>9-3185-3</b>  |
| 550/600  |           | 79.47            | 51.7  | 6.56             | 3.05  | <b>D</b>    |                | <b>9-3185-4</b>  |
| 277  |           | 72.88            | 52.4  | 6.09             | 2.58  | <b>H</b>    |                | <b>9-3185-7</b>  |
| 380/415  | 50        | 64.5             | 50.6  | 6.08             | 2.43  | <b>L</b>    | Class F, 155°C | <b>9-3185-8</b>  |
| <b>15, 25, 30 and 40A – Two- and Three-Pole (Series C1)</b>        |           |                  |       |                  |       |             |                |                  |
| 12   | 60        | 65               | 30    | 11               | 2.5   | <b>R</b>    | Class F, 155°C | <b>9-3125-5</b>  |
| 24   |           | 65               | 30    | 11               | 2.5   | <b>T</b>    |                | <b>9-3125-6</b>  |
| 104/120  |           | 65               | 30    | 11               | 2.5   | <b>A</b>    |                | <b>9-3125-1</b>  |
| 208/240  | 50        | 75               | 35    | 17               | 3.5   | <b>B</b>    | Class F, 155°C | <b>9-3125-2</b>  |
| 440/480  |           | 75               | 35    | 17               | 3.5   | <b>C</b>    |                | <b>9-3125-3</b>  |
| 550/600  |           | 75               | 35    | 17               | 3.5   | <b>D</b>    |                | <b>9-3125-4</b>  |
| 277  | 60        | 65               | 30    | 11               | 2.5   | <b>H</b>    | Class F, 155°C | <b>9-3125-8</b>  |
| 380/415  | 50        | 75               | 35    | 17               | 3.5   | <b>L</b>    | Class F, 155°C | <b>9-3125-8</b>  |