

Replacement classic circuit breakers

Bolt-on Type BQL single-, multi-pole, Duplex, and Quadplex

Type BQL ^a

- 10,000/22,000 A interrupting capacity at 120/240 Vac
- Captive line screw included (#2 Robertson/Slot)

^a HACR rated.

Product selection

Table 77. Single- and multi-pole bolt-on classic replacement circuit breakers

Ampere rating	Wire size range (Cu/Al 60 °C or 75 °C) (AWG)	Catalogue number					
		Single-pole, 120/240 Vac		Two-pole, 120/240 Vac		Three-pole, 120/240 Vac	
		10 kAIC	22 kAIC	10 kAIC	10 kAIC	22 kAIC	
15	#14–8	BQL15 ^a	HBQL15	BQL215	BQL315	HBQL315	
20	#14–8	BQL20 ^a	HBQL20	BQL220	BQL320	—	
25	#14–8	BQL25	HBQL25	BQL225	—	—	
30	#14–8	BQL30	HBQL30	BQL230	BQL330	HBQL330	
40	#14–4	BQL40	HBQL40	BQL240	BQL340	—	
50	#14–4	BQL50	HBQL50	BQL250	BQL350	HBQL350	
60	#8–2/0	BQL60	HBQL60	BQL260	BQL360	HBQL360	
70	#8–2/0	—	—	BQL270	BQL370	HBQL370	
90	#8–2/0	—	—	BQL290	BQL390	HBQL390	
100	#8–2/0	—	—	BQL2100	BQL3100	HBQL3100	
125	#8–2/0	—	—	BQL2125	—	—	
135	#8–2/0	—	—	BQL2135	—	—	
Requires one 1-inch (25.4 mm) space				Requires two 1-inch (25.4 mm) spaces		Requires three 1-inch (25.4 mm) spaces	

^a Switching duty rated (SWD).

Type BQL Duplex and Quadplex ^a

- 10,000 A interrupting capacity at 120/240 Vac
- Captive line screw included (#2 Robertson/Slot)

^a HACR rated.

Table 78. Type BQL Duplex and Quadplex bolt-on classic replacement circuit breakers

Duplex		Quadplex independent trip							
Two single-pole circuits		Two single-pole circuits and one two-pole circuit				Two two-pole circuits			
Ampere rating		Ampere rating				Ampere rating			
		120 Vac		120/240 Vac		120 Vac		120/240 Vac	
120 Vac	Catalogue number	Outer left (single-pole)	Centre (two-pole)	Outer right (single-pole)	Catalogue number	Outer left and right (two-pole)	Centre (two-pole)	Catalogue number	Wire size range (Cu/Al 60 °C or 75 °C) (AWG)
15–15	BQLT15 ^a	15	15	15	BQLT15215	15	15	BQLT215215	#14–4
20–20	BQLT20 ^a	15	20	15	BQLT15220	20	20	BQLT220220	#14–4
30–30	BQLT30 ^a	15	25	15	BQLT15225	15	30	BQLT215230	#14–4
—	—	15	30	15	BQLT15230	15	40	BQLT215240	#14–4
—	—	15	40	15	BQLT15240	—	—	—	#14–4
Requires one 1-inch (25.4 mm) space		Requires two 1-inch (25.4 mm) spaces				Requires two 1-inch (25.4 mm) spaces			

^a Switching duty rated (SWD).

^b ^c Internal common trip.