



**IP44**  
SUITABILITY

## Weatherproof Plates

| Description  | Catalog Number |
|--|----------------|
| Clear bubble plate, silicone rubber for use with all general purpose AC toggle and PresSwitch® Switches. Fits both FS/FD and standard boxes. | <b>HBL1795</b> |



**HBL1795**

## Weatherproof Plates

| Description   | Catalog Number    |
|---|-------------------|
| Gray neoprene PresSwitch® Plate. Fits FS/FD and standard boxes. | <b>HBL1750*</b>   |
| Same as above except yellow.                                    | <b>HBL17CM50*</b> |



**HBL1750**

Note: \*Not UL Listed.

## Weatherproof Plates

| Description   | Catalog Number    |
|---|-------------------|
| Gray neoprene PresSwitch® Plate with 125V red pilot light. Fits only FS/FD boxes. | <b>HBL1785*</b>   |
| Same as above except yellow.  | <b>HBL17CM85*</b> |



**HBL1785**

Note: \*Not UL Listed.

## Weatherproof Covers

| Description  | Catalog Number |
|--|----------------|
| Cast aluminum lift cover plate with fiber shield. For standard toggle and PresSwitch® Switches. Fits only FS/FD boxes. | <b>HBL7420</b> |



**HBL7420**

## Brass Locking Covers Attachment for Switches

| Description   | Catalog Number      |
|---|---------------------|
| Straight keying (all locks alike) appropriate for most applications. Straight cylinder type lock, each HBL96061 ordered operates on the same key—all locks are keyed alike.                       | <b>HBL96061*</b>    |
| Same as above except in dull chrome finish to match stainless steel plates.   | <b>HBL96061DCH*</b> |
| Straight keying (individual). Straight cylinder type lock, each HBL96062 ordered operates on a different key. All locks are keyed differently and individually. This type cannot be master keyed. | <b>HBL96062*</b>    |



**HBL96061**  
shown with wallplate and  
switch (sold separately)

Note: \*Not UL Listed.

## Locking Device

| Description                             | Catalog Number |
|---|----------------|
| Locking device for weatherproof covers. | <b>HBLWLC</b>  |



**HBLWLC**