



### Compact Class CC and Class J

For a complete assembly, please select:

Select for standard applications		<b>Switch</b>												
		<b>Amp rating</b>	<b>Fuse class</b>	<b>Number of poles</b>	<b>SCCR</b>	<b>Max horsepower rating, 3-ph</b>		<b>Wire size</b>	<b>Wire type</b>	<b>Part number</b>				
		30	CC	3	100kA	220/240Vac	440/480Vac	600 Vac	#14-10 Sol/Str	75°C Cu	RDF30CC-3			
		30	CC	3 + Ntrl*	100kA	7.5	15	20	#14-10 Sol/Str	75°C Cu	RDF30CC-3N			
		30	J	3	100kA	7.5	15	20	#14-10 Sol/Str	75°C Cu	RDF30J-3-COMP			
					30	J	3 + Ntrl*	100kA	7.5	15	20	#14-10 Sol/Str	75°C Cu	RDF30J-3N-COMP
	* Neutral is switched.													
	+													
		<b>Direct mount handle - mounts directly to switch, no shaft required</b>												
		<b>For switch part number</b>	<b>Color</b>	<b>Test function</b>	<b>Padlockable</b>					<b>Part number</b>				
RDF30CC- <u>    </u>		Black	Y	Y					DIR-05					
RDF30J- <u>    </u> -COMP		Black	Y	Y					DIR-06					
OR														
	<b>External front operated selector handle - shaft required</b>													
	<b>NEMA type</b>	<b>Color</b>	<b>Test function</b>	<b>Padlockable</b>	<b>Defeatable</b>	<b>Part number</b>								
	1, 3R, 4, 4X, 12	Black	N	Y	Y	H4X-04B								
	1, 3R, 4, 4X, 12	Red/yellow	N	Y	Y	H4X-04R								
	+													
	<b>Shafts for selector handles</b>													
	<b>Length in (mm)</b>	<b>Mounting depth (X) in (mm)</b>						<b>Part number</b>						
	7.9 (200)	4.02~9.65 (102~245)						SH1-200						
	12.6 (320)	4.02~14.37 (102~365)						SH1-320						
	15.7 (400)	4.02~17.52 (102~445)						SH1-400						
OR														
Handle		<b>External front operated pistol handles - shaft required</b>												
		<b>NEMA type</b>	<b>Color</b>	<b>Test function</b>	<b>Padlockable</b>	<b>Defeatable</b>	<b>Part number</b>							
		1, 3R, 12	Black	N	Y	Y	H12-05B							
		1, 3R, 12	Red/yellow	N	Y	Y	H12-05R							
		1, 3R, 4, 4X, 12	Black	N	Y	Y	H4X-05B							
	1, 3R, 4, 4X, 12	Red/yellow	N	Y	Y	H4X-05R								
	1, 3R, 4, 4X, 12	Black	Y	Y	Y	H4X-05TB								
	1, 3R, 4, 4X, 12	Red/yellow	Y	Y	Y	H4X-05TR								
		<b>Metallic hasp (heavy duty) external front operated pistol handles - shaft required</b>												
		<b>NEMA type</b>	<b>Color</b>	<b>Test function</b>	<b>Padlockable</b>	<b>Defeatable</b>	<b>Part number</b>							
1, 3R, 4, 4X, 12		Black	N	Y	Y	H4X-05BHD								
1, 3R, 4, 4X, 12		Red/yellow	N	Y	Y	H4X-05RHD								
+														
	<b>Shafts for pistol handles</b>													
	<b>Length in (mm)</b>	<b>Mounting depth (X) in (mm)</b>						<b>Part number</b>						
	7.9 (200)	4.02~9.65 (102~245)						SH2-200						
	12.6 (320)	4.02~14.37 (102~365)						SH2-320						
	15.7 (400)	4.02~17.52 (102~445)						SH2-400						
OR														
	<b>NFPA through the door handle kit - to be used with front pistol handle</b>													
	<b>Color</b>	<b>Test function</b>	<b>Padlockable</b>	<b>Defeatable</b>	<b>Part number</b>									
Red	N	Y	N	H79-1										
and...														
Accessories		<b>Auxiliary contacts</b>												
		<b>Contact type</b>	<b>Number of contacts</b>	<b>Continuous amp rating</b>	<b>Voltage rating</b>	<b>Maximum number of auxiliary contacts per disconnect switch part number</b>			<b>Part number</b>					
		NO	1	10A	600Vac	RDF30CC- <u>    </u> : 4 / 8 with BAC-HOLDER2			BAC05 <sup>(1)</sup>					
		NC	1	10A	600Vac	RDF30J- <u>    </u> -COMP: 2 / 6 with BAC-HOLDER2			BAC06 <sup>(1)</sup>					
Auxiliary Contact Holder				Accepts 4 Auxiliary contacts: BAC05 or BAC06			BAC-HOLDER2 <sup>(2)</sup>							