



### Standard Class J

For a complete assembly, please select:

SWITCH		<b>Switch</b>												
		<b>Amp rating</b>	<b>Fuse class</b>	<b>No. of poles</b>	<b>SCCR</b>	<b>Max horsepower rating</b>					<b>Wire size</b>	<b>Wire type</b>	<b>Part number</b>	
						<b>1-phase 220/240Vac</b>	<b>3-phase</b>		<b>DC*</b>					
						<b>220/240Vac</b>	<b>440/480Vac</b>	<b>600 Vac</b>	<b>125 Vdc</b>	<b>250 Vdc</b>				
30	J	2	200kA	3	-	-	-	3	5	#14-10 Sol #14-6 Str	75°C Cu	RDF30J-2		
30	J	3	200kA	-	7.5	15	20	3	5	#14-10 Sol #14-6 Str	75°C Cu	RDF30J-3		
30	J	4	200kA	-	7.5	15	20	3	5	#14-10 Sol #14-6 Str	75°C Cu	RDF30J-4		
* DC ratings use two poles in series.														
+														
Select for standard applications		<b>Direct mount handle - mounts directly to switch, no shaft required</b>												
		<b>For switch Part number</b>	<b>Color</b>		<b>Test function</b>	<b>Padlockable</b>						<b>Part number</b>		
		All switches	Black		Y	Y - On Switch						DIR-07		
		OR												
		 or 	<b>External front operated pistol handles - shaft required</b>											
			<b>NEMA type</b>	<b>Color</b>		<b>Test function</b>	<b>Padlockable</b>	<b>Defeatable</b>					<b>Part number</b>	
			1, 3R, 12	Black		N	Y	Y					H12-05B	
			1, 3R, 12	Red/yellow		N	Y	Y					H12-05R	
			1, 3R, 4, 4X, 12	Black		N	Y	Y					H4X-05B	
			1, 3R, 4, 4X, 12	Red/yellow		N	Y	Y					H4X-05R	
1, 3R, 4, 4X, 12	Black		Y	Y	Y					H4X-05TB				
1, 3R, 4, 4X, 12	Red/yellow		Y	Y	Y					H4X-05TR				
<b>Metallic hasp (heavy duty) external front operated pistol handles - shaft required</b>														
<b>NEMA type</b>	<b>Color</b>		<b>Test function</b>	<b>Padlockable</b>	<b>Defeatable</b>					<b>Part number</b>				
1, 3R, 4, 4X, 12	Black		N	Y	Y					H4X-05BHD				
1, 3R, 4, 4X, 12	Red/yellow		N	Y	Y					H4X-05RHD				
<b>External right side operated pistol handles - shaft required</b>														
<b>NEMA type</b>	<b>Color</b>		<b>Test function</b>	<b>Padlockable</b>	<b>Defeatable</b>					<b>Part number</b>				
1, 3R, 4, 4X, 12	Black		N	Y	N/A					H4X-05SB				
1, 3R, 4, 4X, 12	Red/yellow		N	Y	N/A					H4X-05SR				
<b>Shafts for pistol handles</b>														
<b>Length in (mm)</b>	<b>Mounting depth (X) in (mm)</b>										<b>Part number</b>			
7.9 (200)	5.30~9.06 (135~230)										SH5-200			
12.6 (320)	5.30~13.78 (135~350)										SH5-320			
15.7 (400)	5.30~16.93 (135~430)										SH5-400			
OR														
	<b>Flange handle<sup>(1)</sup> - requires shaft operated mechanism or cable operated mechanism + cable</b>													
	<b>NEMA type</b>	<b>Flange style</b>		<b>Test function</b>	<b>Padlockable</b>	<b>Defeatable</b>					<b>Part number</b>			
	1, 3R, 4, 12	Standard		N	Y	Y					FLH1			
	1, 3R, 4, 4X, 12	Chrome Plated		N	Y	Y					FLH2			
	<b>Shaft operated flange mechanism<sup>(2)</sup> - includes shaft</b>													
	<b>For enclosure depth - in (mm)</b>									<b>Part number</b>				
	6~24 (152~613)									FLRM				
	<b>Cable operated flange mechanism and cable - must select mechanism<sup>(3)</sup> and cable<sup>(4)</sup></b>													
	<b>Item / length</b>									<b>Part number</b>				
	Cable mechanism									FLCM				
36" (900mm) cable									FLC36					
60" (1500mm) cable									FLC60					
120" (3000mm) cable									FLC120					
OR														
	<b>NFPA through the door handle kit - to be used with front pistol handle</b>													
	<b>Color</b>			<b>Test function</b>	<b>Padlockable</b>	<b>Defeatable</b>					<b>Part number</b>			
Red			N	Y	N					H79-2				