

### Standard Class J

For a complete assembly, please select:

SWITCH + LUGS		<b>Switch</b>										
		Amp rating	Fuse class	Number of poles	SCCR	Max horsepower rating				DC*		Part number
						1-phase 220/240Vac	220/240Vac	3-phase 440/480Vac	600 Vac	125 Vdc	250 Vdc	
		200	J	2	200kA	10	-	-	-	-	-	RDF200J-2
		200	J	3	200kA	-	60	125	150	-	-	RDF200J-3
		200	J	4	200kA	-	60	125	150	-	-	RDF200J-4
		400	J	2	200kA	10	-	-	-	20	50	RDF400J-2
		400	J	3	200kA	-	125	250	350	20	50	RDF400J-3
		400	J	4	200kA	-	125	250	350	20	50	RDF400J-4
		* DC ratings use two poles in series.										
HANDLE		<b>Terminal lug kit</b>										
		Switch amp rating	Number of poles	Lugs Per kit	Wire range				Wire type	Part number		
		200	2	2	#6-300MCM				75°C Cu/Al	LUG1-2		
		200	3	3	#6-300MCM				75°C Cu/Al	LUG1-3		
		200	4	4	#6-300MCM				75°C Cu/Al	LUG1-4		
		400	2	2	#4-600MCM or Dual 1/0-250MCM				75°C Cu/Al	LUG2-2		
		400	3	3	#4-600MCM or Dual 1/0-250MCM				75°C Cu/Al	LUG2-3		
		400	4	4	#4-600MCM or Dual 1/0-250MCM				75°C Cu/Al	LUG2-4		
		+										
			<b>Direct mount handle - mounts directly to switch, no shaft required</b>									
For switch Part number	Color		Test function	Padlockable						Part number		
All switches		Black	Y	Y						DIR-07		
or												
	<b>External front operated pistol handles - shaft required</b>											
	NEMA type	Color	Test function	Padlockable	Defeatable	Part number						
	1, 3R, 12	Black	N	Y	Y	H12-03B						
	1, 3R, 12	Red/yellow	N	Y	Y	H12-03R						
	1, 3R, 4, 4X, 12	Black	N	Y	Y	H4X-06B						
	1, 3R, 4, 4X, 12	Red/yellow	N	Y	Y	H4X-06R						
	1, 3R, 4, 4X, 12	Black	Y	Y	Y	H4X-06TB						
	1, 3R, 4, 4X, 12	Red/yellow	Y	Y	Y	H4X-06TR						
	or											
		<b>Metallic hasp (heavy duty) external front operated pistol handles - shaft required</b>										
NEMA type		Color	Test function	Padlockable	Defeatable	Part number						
1, 3R, 4, 4X, 12		Black	N	Y	Y	H4X-06BHD						
1, 3R, 4, 4X, 12	Red/yellow	N	Y	Y	H4X-06RHD							
	<b>External right side operated pistol handles - shaft required</b>											
	NEMA type	Color	Test function	Padlockable	Defeatable	Part number						
	1, 3R, 4, 4X, 12	Black	N	Y	N/A	H4X-06SB						
	1, 3R, 4, 4X, 12	Red/yellow	N	Y	N/A	H4X-06SR						
	<b>Shafts for pistol handles</b>											
	Length in (mm)	Mounting depth (X) in (mm)								Part number		
	7.9 (200)	200A: 5.70-9.06 (145-230) 400A: 7.87-10.24 (200-260)								SH5-200		
	12.6 (320)	200A: 5.70-13.78 (145-350) 400A: 7.87-16.93 (200-380)								SH5-320		
	15.7 (400)	200A: 5.70-16.93 (145-430) 400A: 7.87-18.10 (200-460)								SH5-400		