

















For use with	Rated control voltage U_s V	Part no. Article no. when ordered separately	Price See price list	Std. pack	Notes					
Shunt releases										
With early-make auxiliary contact										
Not in combination with remote operator.										
 	With clamp terminal on left switch side.	NZM1(-4), N(S)1(-4)	12 V AC/DC	NZM1-XAHIV12AC/DC 259772	1 off  	When the shunt release is live, contact with the switch's main contacts on switching on is reliably prevented. Early make of auxiliary contact on switching on and off (manual operation): approx. 20 ms. Undervoltage release cannot be installed simultaneously with early-make auxiliary contact NZM...-XHIV... or undervoltage release NZM...-XU...				
			24 V AC/DC	NZM1-XAHIV24AC/DC 259774						
			48 V AC/DC	NZM1-XAHIV48AC/DC 259776						
			60 V AC/DC	NZM1-XAHIV60AC/DC 259778						
			110 V-130 V AC/DC	NZM1-XAHIV110-130AC/DC 259780						
			208 V-250 V AC/DC	NZM1-XAHIV208-250AC/DC 259782						
			380 V-440 V AC/DC	NZM1-XAHIV380-440AC/DC 259784						
 	With 3 m connection cable instead of screw connection	NZM1(-4), N(S)1(-4)	12 V AC/DC	NZM1-XAHIVL12AC/DC 259790	1 off  					
			24 V AC/DC	NZM1-XAHIVL24AC/DC 259792						
			110 V-130 V AC/DC	NZM1-XAHIVL110-130AC/DC 259798						
			208 V-250 V AC/DC	NZM1-XAHIVL208-250AC/DC 259800						
			380 V-440 V AC/DC	NZM1-XAHIVL380-440AC/DC 259802						
			 	NZM2(-4), N(S)2(-4) NZM3(-4), N(S)3(-4)			12 V AC/DC	NZM2/3-XAHIV12AC/DC 259808	1 off  	
							24 V AC/DC	NZM2/3-XAHIV24AC/DC 259810		
48 V AC/DC	NZM2/3-XAHIV48AC/DC 259812									
60 V AC/DC	NZM2/3-XAHIV60AC/DC 259814									
110 V-130 V AC/DC	NZM2/3-XAHIV110-130AC/DC 259816									
208 V-250 V AC/DC	NZM2/3-XAHIV208-250AC/DC 259818									
380 V-440 V AC/DC	NZM2/3-XAHIV380-440AC/DC 259820									
 	NZM4(-4), N(S)4(-4)	12 V AC/DC	NZM4-XAHIV12AC/DC 266470	1 off  	When the shunt release is live, contact with the switch's main contacts on switching on is reliably prevented. Early make of auxiliary contact on switching on (manual operation): approx. 90 ms. Cannot be used in conjunction with remote operator NZM...-XR.... Undervoltage release cannot be installed simultaneously with early-make auxiliary contact NZM...-XHIV... or undervoltage release NZM...-XU...					
		24 V AC/DC	NZM4-XAHIV24AC/DC 266471							
		48 V AC/DC	NZM4-XAHIV48AC/DC 266472							
		60 V AC/DC	NZM4-XAHIV60AC/DC 266473							
		110 V-130 V AC/DC	NZM4-XAHIV110-130AC/DC 266474							
		208 V-250 V AC/DC	NZM4-XAHIV208-250AC/DC 266475							
		380 V-440 V AC/DC	NZM4-XAHIV380-440AC/DC 266476							

Information relevant for export to North America



Product Standards
UL File No.
UL CCN
CSA File No.
CSA Class No.
NA Certification

UL489; CSA-C22.2 No. 5-09; IEC60947, CE marking
E140305
DIHS
Q22086
1437-01
UL Listed, CSA certified