








Contact configuration		Contact sequence	housing	Cage Clamp ¹⁾	Screw terminal
⊕ Positive opening safety function according to IEC/EN 60947-5-1					
N/O = normally open contact	N/C = normally closed contact			Part no. Article no.	Part no. Article no.

Basic device, expandable						
Analog electronic position switches IP66, IP67						
no safety function Visual status display Q1 = analog output Q2 = Diagnostics output			Insulated material	LSE-AI 269461		
			Insulated material	LSE-AU 274096		
IP66, IP67 operating point electronically adjustable						
Visible status display, comparable with positive opening function partly short-circuit proof, restart after reset						
						
	1 N/O	1 N/C		Insulated material	LSE-11 266121	
	-	2 N/C		Insulated material	LSE-02 266122	
Rounded plunger, IP66, IP67						
	-	2 N/C		Insulated material	LS-02 266107	LS-S02 106729
	-	2 N/C		Metal	LSM-02 266142	-
	1 N/O	1 N/C		Insulated material	LS-11 266109	LS-S11 106783
	1 N/O	1 N/C		Metal	LSM-11 266144	-
with quick-break switch	1 N/O	1 N/C		Insulated material	LS-11S 266105	LS-S11S 106798
	1 N/O	1 N/C		Metal	LSM-11S 266140	-
Rounded plunger, IP66, IP67 (without positive opening)						
	2 N/O	-		Insulated material	LS-20 266120	LS-S20 106808
	2 N/O	-		Metal	LSM-20 266155	-

Notes

¹⁾ Cage-Clamp is a registered trademark of Wago Kontakttechnik, 32432 Minden, Germany.
Accessories for the Cage Clamp terminals from Wago:
Jumper insert, grey, Wago article no. 264-402