



Hart lock industrial grade 20A locking devices

Product description

3-pole, 4-wire grounding
20A, 3Ø 250V/AC
NEMA L15-20



AHL1520P



AHL1520C



AHL1520R

Industrial grade plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	250	L15-20	3Ø ultra grip straight body	0.38-1.16" (9.5-29.4mm)	BK & W	□ AHL1520P	□ AHL1520C	•	•

Industrial grade receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle		
20	250	L15-20	3Ø standard industrial	BK	□ AHL1520R ^a	•	•
			3Ø isolated ground	RN	□ IGL1520R*	•	•

*Not Fed Spec, ^aNot NOM cert

Industrial grade flanged inlets & outlets

Rating A	V/AC	NEMA	Description	Color	Flanged inlet	Flanged outlet		
20	250	L15-20	3Ø standard industrial	BK	□ AHL1520FI	—	•	•
			3Ø standard industrial	BK & W	—	□ AHL1520FO ^{††}	•	•

^{††}UL Listed only

Accessories for L15-20 locking devices

Description	Catalog no.		
Neoprene weather protective boot for 4-W & 5-W plugs	□ BL1	•	•
Neoprene weather protective boot for 4-W & 5-W connectors	□ BL2	•	•
Diecast aluminum single receptacle cover, vertical mount, for FS/FD boxes	□ 7420	•	•
Glass-filled nylon flanged inlet/outlet cover, vertical mount, for 20A devices	□ WP2	•	•



BL1



BL2



7420



WP2

Dimensional information:
C-76-C-78

Plug & connector specification information:
Ultra grip K15-20: C-84

Receptacle specification information:
K15-20: C-87

Isolated ground K15-20: C-87
Flanged inlet & flanged outlet specification information:
K15-20: C-89

Color information:

BK (Black), RN (Orange), W (White)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-30

RoHS compliant - Page Q-30