













Moeller SK1230-1157GB-INT

For use with	Standard Part no. Article no. when ordered separately	Price see price list	Std. pack	Notes
Door coupling rotary handle				
Complete including rotary drive and coupling parts Extension shaft additionally required. Degree of protection IP66/UL/CSA Type 4X				
Standard, black/grey				
	Lockable in 0 position on handle. With door interlock	NZM1, N1 NZM2, N2 NZM3, N3 NZM4, N4	NZM1-XTVD-NA 271445 NZM2-XTVD-NA 271446 NZM3-XTVD-NA 271447 NZM4-XTVD-NA 271448	1 off Door interlock • Non defeatable in the locked OFF position. • Door opening possible after active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on
	Lockable on handle and switch. Can be locked in 0 position, with adequate modification also in I position. With door interlock Lockable in 0 position on breaker.	NZM1, N1 NZM2, N2 NZM3, N3 NZM4, N4	NZM1-XTVDV-NA 100683 NZM2-XTVDV-NA 100684 NZM3-XTVDV-NA 100685 NZM4-XTVDV-NA 100686	1 off Door interlock • Not defeatable in the locked OFF position • Door opening possible with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on
	Lockable on handle and switch. Lockable in 0 position on handle. With door interlock Lockable in 0 position on breaker.	NZM1, N1 NZM2, N2 NZM3, N3 NZM4, N4	NZM1-XTVDVR-NA 271449 NZM2-XTVDVR-NA 271450 NZM3-XTVDVR-NA 271451 NZM4-XTVDVR-NA 271452	1 off Door interlock • Not defeatable in the locked OFF position • Door opening possible with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on
Red-yellow for Emergency-Stop				
	Lockable on handle and switch. Lockable in 0 position on handle. With door interlock Lockable in 0 position on breaker.	NZM1, N1 NZM2, N2 NZM3, N3 NZM4, N4	NZM1-XTVDVR-NA 271449 NZM2-XTVDVR-NA 271450 NZM3-XTVDVR-NA 271451 NZM4-XTVDVR-NA 271452	1 off Door interlock • Not defeatable in the locked OFF position • Door opening possible with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on
	Lockable on handle and switch. Lockable in 0 position on handle. With door interlock Lockable in 0 position on breaker.	NZM1, N1 NZM2, N2 NZM3, N3 NZM4, N4	NZM1-XTVDVR-NA 271449 NZM2-XTVDVR-NA 271450 NZM3-XTVDVR-NA 271451 NZM4-XTVDVR-NA 271452	1 off Door interlock • Not defeatable in the locked OFF position • Door opening possible with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on
Extension shaft				
	Max. mounting depth: 400 mm	NZM1(-4), PN1(-4), N1(-4) NZM2(-4), PN2(-4), N2(-4) NZM3(-4), PN3(-4), N3(-4) NZM4(-4), N4(-4)	NZM1/2-XV4 261232 NZM3/4-XV4 261234	1 off Can be cut to required length
	Max. mounting depth: 600 mm	NZM1(-4), PN1(-4), N1(-4) NZM2(-4), PN2(-4), N2(-4) NZM3(-4), PN3(-4), N3(-4) NZM4(-4), N4(-4)	NZM1/2-XV6 260191 NZM3/4-XV6 260193	

Notes Circuit-breaker can also be installed in a lying position 90° left/right, with the handle still in the same position.

Moeller SK1230-1157GB-INT

For a max. shaft length of 60 mm	Part no. Article no. when ordered separately	Price see price list	Notes	Extremely narrow fittings	Part no. Article no. when ordered separately	Price see price list	Std. pack	Notes
Door coupling rotary handle								
Complete including rotary drive and coupling parts Extension shaft additionally required. Degree of protection IP66/UL/CSA Type 4X								
Standard, black/grey								
	Lockable in 0 position on handle. With door interlock	NZM1, N1 NZM2, N2 NZM3, N3 NZM4, N4	NZM1-XTVD-NA 271445 NZM2-XTVD-NA 271446 NZM3-XTVD-NA 271447 NZM4-XTVD-NA 271448	1 off Door interlock • Non defeatable in the locked OFF position. • Door opening possible after active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on				
	Lockable on handle and switch. Can be locked in 0 position, with adequate modification also in I position. With door interlock Lockable in 0 position on breaker.	NZM1, N1 NZM2, N2 NZM3, N3 NZM4, N4	NZM1-XTVDV-NA 100683 NZM2-XTVDV-NA 100684 NZM3-XTVDV-NA 100685 NZM4-XTVDV-NA 100686	1 off Door interlock • Not defeatable in the locked OFF position • Door opening possible with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on				
	Lockable on handle and switch. Lockable in 0 position on handle. With door interlock Lockable in 0 position on breaker.	NZM1, N1 NZM2, N2 NZM3, N3 NZM4, N4	NZM1-XTVDVR-NA 271449 NZM2-XTVDVR-NA 271450 NZM3-XTVDVR-NA 271451 NZM4-XTVDVR-NA 271452	1 off Door interlock • Not defeatable in the locked OFF position • Door opening possible with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on				
Red-yellow for Emergency-Stop								
	Lockable on handle and switch. Lockable in 0 position on handle. With door interlock Lockable in 0 position on breaker.	NZM1, N1 NZM2, N2 NZM3, N3 NZM4, N4	NZM1-XTVDVR-NA 271449 NZM2-XTVDVR-NA 271450 NZM3-XTVDVR-NA 271451 NZM4-XTVDVR-NA 271452	1 off Door interlock • Not defeatable in the locked OFF position • Door opening possible with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on				
	Lockable on handle and switch. Lockable in 0 position on handle. With door interlock Lockable in 0 position on breaker.	NZM1, N1 NZM2, N2 NZM3, N3 NZM4, N4	NZM1-XTVDVR-NA 271449 NZM2-XTVDVR-NA 271450 NZM3-XTVDVR-NA 271451 NZM4-XTVDVR-NA 271452	1 off Door interlock • Not defeatable in the locked OFF position • Door opening possible with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on				
Extension shaft								
	Max. mounting depth: 400 mm	NZM1(-4), PN1(-4), N1(-4) NZM2(-4), PN2(-4), N2(-4) NZM3(-4), PN3(-4), N3(-4) NZM4(-4), N4(-4)	NZM1/2-XV4 261232 NZM3/4-XV4 261234	1 off Can be cut to required length				
	Max. mounting depth: 600 mm	NZM1(-4), PN1(-4), N1(-4) NZM2(-4), PN2(-4), N2(-4) NZM3(-4), PN3(-4), N3(-4) NZM4(-4), N4(-4)	NZM1/2-XV6 260191 NZM3/4-XV6 260193					

Notes Circuit-breaker can also be installed in a lying position 90° left/right, with the handle still in the same position.

Circuit-breakers, switch-disconnectors up to 1600 A

Circuit-breakers, switch-disconnectors up to 1600 A